T H E U N I V E R S I T Y O F A L B E R T A

RELEASE FORM

NAME OF AUTHOR CHRISTIAAN WILLEM LUURSEMA

TITLE OF THESIS PERTURBED ANGULAR DISTRIBUTION ON THE 879 keV LEVEL IN ^{70}Ga

DEGREE FOR WHICH THESIS WAS PRESENTED MASTER OF SCIENCE

YEAR THIS DEGREE GRANTED 1975

THE UNIVERSITY OF ALBERTA

PERTURBED ANGULAR DISTRIBUTION ON THE 879 keV LEVEL IN ^{70}Ga

by

© CHRISTIAAN WILLEM LUURSEMA

A THESIS

SUBMITTED TO THE FACULTY OF GRADUATE STUDIES AND RESEARCH

IN PARTIAL FULFILMENT OF THE REQUIREMENTS FOR THE DEGREE

OF MASTER OF SCIENCE

DEPARTMENT OF PHYSICS

EDMONTON, ALBERTA

FALL, 1975

THE UNIVERSITY OF ALBERTA

FACULTY OF GRADUATE STUDIES AND RESEARCH

The undersigned certify that they have read, and recommend to the Faculty of Graduate Studies and Research, for acceptance, a thesis entitled "A Perturbed Angular Distribution on the 879 keV Level in ^{70}Ga" submitted by Christiaan Willem Luursema in partial fulfilment of the requirements for the degree of Master of Science.

ABSTRACT

This work deals with the time-dependent quadrupole interaction of ^{70}Ga in a Zn lattice for the 879 keV level with spin 4.

The quadrupole frequency has a value $\omega_q = e^2qQ/\hbar$ = 315 MHz and it changes (+3 ± 6)% from 300 K to 600 K. The derived quadrupole moment is 0.5 b when the field gradient is estimated according to the proposed universal correlation between the local and lattice part of the field gradient. The temperature dependence might indicate a larger quadrupole moment.

The measured anisotropy coefficients are consistent with a CN-model for spin 4 and the published anisotropies of the decay of the 1102 keV level with spin 4^-.

The time-integrated values of the attenuation coefficients give in combination with the unperturbed values the indication that the assumption of a static electric field gradient is probably not correct for all nuclei at higher temperatures.

The measurements do not yield a definite value of the spin of the 879 keV level or of the asymmetry parameter η.

ACKNOWLEDGEMENTS

I would like to thank Dr. Dave Hutcheon for his enormous help in all aspects of this work.

I greatly appreciate discussions with my supervisor, Dr. Sheppard, in all phases of my work.

I wish to thank Dr. J. T. Sample and Dr. R. Lawson for their work on my committee.

The help of Jock Elliot in operating the machine was always much appreciated and necessary.

I would like to thank the rest of the staff, academic and non-academic, for the various ways in which they helped me.

My sincere thanks to Mrs. Wahl and graphics for the marvelous job they did on the technical perfection of this thesis.

TABLE OF CONTENTS

LIST OF TABLES

LIST OF FIGURES

CHAPTER I

INTRODUCTION

When a nucleus in an excited state is formed in a reaction, the population of the magnetic substates is not necessarily equal, but the nucleus may be aligned. This causes the decay of the nucleus to be anisotropic. The degree of anisotropy yields information about the spins and of the levels involved in the decay. When the excited state formed has an electric or magnetic multipole moment and experiences an appropriate field for this moment, it will precess. This is the well-known Larmor precession for the case of the magnetic dispoles. This precession will also rotate the angular distribution of the decay of the level. To see the effect of the precession the level has to have a lifetime. The technique which looks at the time-dependence of this precession in times longer than five nanoseconds is called time-dependent perturbed angular distribution method.

This thesis describes studies of pertubation of γ ray angular distributions due to the interaction of the nuclear quadrupole moment and the electric field gradient (E.F.G.) at the nuclear site.

The interaction is characterized by the spin of the level and the quadrupole frequency $e^2qQ/\bar{h}$, where eq is the largest component of the field gradient and Q is the quadrupole

moment of the nucleus. All three parameters are obtainable from a time-dependent angular correlation or distribution measurement (TDPAC or TDPAD). In the correlation experiment the nucleus is aligned by the detected first decay, which feeds the level, and the angular distribution of the second decay, depopulating the level, is measured. The distribution experiments involves the nucleus aligned in a reaction. TDPAC is the most applied technique of these two, for TDPAD experiments require a pulsed beam to define the time of creation of the level, while TDPAC uses the populating decay as time reference point. University of Alberta has a pulsed beam with a width of 1 ns and the level of interest is not populated by a long-lived parent, TDPAD was the way to perform these experiments.

Since the frequency is a product of two unknown quantities, i.e. q and Q, the results of one measurement don't yield definite values for both quantities. By looking at the behaviour at various temperatures or in different hosts or compare the value of the frequency with those of other ions in the same host, one is able to obtain more information about the various contributions to the field gradient, i.e. the lattice part, the local part and radiation damage. The other possibility to calculate one value and deduce the other is up to the present, in most cases, impossible.

Three sets of measurements were carried out. The first concerned the interaction of ^{70}Ga in a metallic Zn

target. In the study of the spin and parities of levels in the isotope ^{70}Ga there appeared a discrepancy between the data obtained from particle work and the γ ray anisotropy of the 879 keV level (Do72). Since this level has a halflife of 23 ns, and the Zn target used in the γ ray study is non-cubic there is the possibility of a pertubation of the anisotropy due to a quadrupole interaction. The other collaborators of the published paper (Hu75) had measured the time dependence of the anisotropy at room temperature. In order to estimate the effects of radiation damage the measurements were extended to investigate the temperature dependence of the interaction.

Two experiments in addition to the interaction of Ga in Zn, were begun. One was an attempt to measure the quadrupole interaction of ^{70}Ga in Ga metal, the other an experiment to compare the quadrupole interactions of ^{18}F(1121 keV level) and ^{19}F (197 keV, Q = 0.11 b). Both these experiments need only the final data-taking, but this was prevented by a major shutdown of the beam-line.

For the experiments various requirements were present, especially for the target chamber. The Ga in Zn experiment had no particular requirement for the room temperature run, but for the study of temperature dependence a hot target chamber was developed, which was capable of keeping the target at a well defined temperature as high as 600 K, did not produce background radiation and showed isotropic absorption.

The annihilation radiation of the decay of $^{18}F(T_{1/2}= 110$ min.) produced so much background, that it was necessary to shield a part of this radiation from the detectors. This was done with the background supressing target holder, which uses up to 5 targets in the same measurement. The Ga in Ga metal experiment required a cooling device, because the melting point of Ga is only 29.8°C and the purpose was to look at a solid target. It also required the use of a less efficient detector, for the yield of the reaction of interest was very high. The Low Energy Photon Spectrometer (LEPS) detector was used for this purpose.

All experiments were analyzed with the assumption that the interaction originated from a static electric field gradient. This assumption implies that the radiation damage either is neglibible or is "frozen in" for a time long compared to the lifetime of the level of interest. This was justified by the measurements of Bleck et al. (Bl72) and McDonald et al. (Mc72). But the results of this work indicate that the field gradient experienced by the nuclei is probably not static for all nuclei.

CHAPTER II

THEORY OF QUADRUPOLE INTERACTION

II.1 Angular Distributions

In the derivations we follow the sign conventions and definitions of Rose and Brink [Ro67] and Brink and Satchler [Br62].

A nuclear state with spin I, can be completely described with a density matrix ρ, whose matrix elements are defined by

$$\rho_{mm'} = \langle I\ m|\ \rho\ |I\ m'\rangle$$

One can expand the density-matrix in so-called statistical tensors ρ^{λ}_{q}

$$\langle I\ m|\ \rho\ |I\ m'\rangle = \sum_{\lambda} \rho^{\lambda}_{q} (I\ -m\ I\ m'|\lambda\ q)(-1)^{\lambda-I-m} \qquad (II.1)$$

or

$$\rho^{\lambda}_{q} = \sum_{m} (-1)^{\lambda-I-m} (I\ -m\ I\ m'|\lambda\ q) \langle I\ m|\ \rho\ |I\ m'\rangle \qquad (II.2)$$

These statistical tensors behave under rotation over the Euler angles α, β, γ (Fig. 1) as

$$(\rho')^{\lambda}_{q'} = \sum_{q} \rho^{\lambda}_{q} D^{\lambda}_{qq'}(\alpha\beta\gamma) \qquad (II.3)$$



Fig. 1: Euler angles α rotation around the z - axis
β rotation around the y_1- axis
γ rotation around the z'- axis

where $D^{\lambda}_{qq'}(\alpha\beta\gamma)$ is the rotation matrix.

When we look at systems with cylindrical symmetry around the Z-axis a rotation around the z-axis will not change the density matrix. Such a rotation is $\alpha \neq 0$, $\beta = 0$, $\gamma = 0$ and $D^{\lambda}_{qq'}(\alpha,0,0) = e^{-iq\alpha}\delta_{qq'}$

and

$$(\rho')^{\lambda}_{q'} = \Sigma_q \, e^{-i\alpha q}\delta_{qq'} \, \rho^{\lambda}_{q}$$

$$= e^{-iq'\alpha} \, \rho^{\lambda}_{q'}\delta_{qq'}$$

But $(\rho')^{\lambda}_{q} = \rho^{\lambda}_{q}$

which means that only the terms with $q = 0$ do not disappear.

The remaining terms are simply related to the alignment parameters $B_{\lambda}(I)$ as defined by Ro67 by

$$\rho^{\lambda}_{o}(I) = \frac{1}{(2I+1)^{\frac{1}{2}}} B_{\lambda}(I) \qquad (II.4)$$

When a state as described above decays with a γ - ray to a state with spin I_2 we have an angular distribution as derived in Ro67

$$W(\theta) = \Sigma_k \text{ even } B_k(I_1) \, R_k(I_1 I_2) \, P_k(\cos\theta), \qquad (II.5)$$

where $P_k(\cos\theta)$ is the Legendre polynomial in the cosine of the angle with the z-axis.

$R_k(I_1 I_2)$ transition dependent parameter.

$$R_k(I_1I_2) = \Sigma_{(L\pi)(L'\pi')} \frac{\{R_k(LL'I_1I_2)\ \delta_L^{<\pi>}\ \delta_{L'}^{<\pi'>}\}}{\Sigma_L |\ \delta_L^{<\pi>}\ |^2} \qquad (II.6)$$

$R_k(LL'I_1I_2)$ is a product of Clebsch-Gordan and Racah coefficients (see formula 3.31 of Ro67).

L and L' are the allowed multipolarities of the decay and $<\pi>$ indicate an Electric or Magnetic transition.

$\delta^{<\pi>}$ is the so-called mixing-ratio defined by

$$\delta_L^{<\pi>} = \frac{<I_1 ||\ T_L^{<\pi>}\ ||I_2>/(2L+1)}{<I_1 ||\ T_{\bar{L}}^{<\pi>}\ ||I_2>/(2\bar{L}+1)} \qquad (II.7)$$

where $T_L^{<\pi>}$ is the transition-operator for the $L^{<\pi>}$ transition and $\bar{L}$ the lowest-order multipolarity in the transition. The angular distribution of the second γ -ray from the state with spin I_2 to the state with spin I_3 is given by

$$W(\theta) = \Sigma_k\ B_k(I)\ R_k(I_2I_3)\ U_k(I_1I_2)\ P_k(\cos\theta) \qquad (II.8)$$

with $U_k(I_1I_2) = \Sigma_{L_{12}}\ (\delta_{L_{12}})^2\ U_k(L_{12}I_1I_2) \ /\ \Sigma(\delta_{L_{12}})^2$

$$U_k(L_{12}I_1I_2) = (-1)^k\ \frac{W(I_1I_1I_2I_2;k\ L_{12})}{W(I_1I_1I_2I_2;0\ L_{12})}\ , \qquad (II.9)$$

where W is the Racah coefficient and

L_{12} is the multipolarity of the γ-decay from I_1 to I_2. Usually and also here we take only mixing between two multipolarities, for the transition probability becomes negligibly smaller with higher multipolarity.

Formula II.8 is only valid if the state with spin I_2 is unperturbed, i.e. the lifetime is short compared to the time in which an interaction can disturb the density matrix.

For practical purposes the angular distributions are described by

$$W(\theta) = A_o \Sigma_k \text{ even } a_k P_k (\cos\theta) \qquad \text{(II.10)}$$

where

$$a_k = \frac{B_k U_k R_k}{B_o U_o R_o} \qquad \text{(II.11)}$$

($U_k = 1$ when we observe the first decay and R_k is the value for the observed decay).

When level 1 is perturbed, i.e. has a time-dependent density matrix, we end up with a time-dependent angular distribution for both decays.

$$\begin{aligned} W(\theta) &= A_o \Sigma_k a_k(t) P_k (\cos\theta) \\ &= \Sigma_k B_k(I,t) U_k R_k P_k(\cos\theta) \\ &= \Sigma_k B_k(I,0) U_k R_k P_k(\cos\theta) G_k(t) \\ &= A_o \Sigma_k a_k G_k(t) U_k R_k P_k(\cos\theta) \qquad \text{(II.12)} \end{aligned}$$

Where $G_k(t) \equiv \frac{a_k(t)}{a_o(0)}$

From this we see that the second decay, for which in general $U_k \neq 1$, has the same time-dependence as the first decay, only

the unperturbed value $a_k(0)$ will be different.

II.2 Perturbed Angular Distribution

The expression for $G_k(t)$ can be evaluated for any case with a known interaction-Hamiltonian, which is time-dependent in one system. From (II.2) and (II.4) follows

$$G_k(t) = \frac{a_k(t)}{a_k(0)} = \frac{B_k(I,t)}{B_k(I,0)} = \frac{\rho^k(t)}{\rho^k(0)} \qquad \text{(II.13)}$$

In solving the expression for G we have to work in three coordinate systems:

(a) The laboratory system, which is defined by the plane of detection. In this system, $a_k(0)$ and $G_k(t)$ are defined.

(b) The "creation" system. In this system we know the density matrix as formed by the beam and subsequent reaction, or any other method.

(c) The crystal system, which gives us the interaction-Hamiltonian, defined by an externally applied field or hyperfine fields.

To calculate $G_k(t)$ we follow the following procedure:

(1) Transform $\rho_q^\lambda(t)$ from the laboratory system to the crystal system.

(2) Form the density matrix in the crystal system.

(3) Calculate the time-dependence in this system of the density matrix as function of the density matrix at time zero.

(4) Expand the time zero density matrix in statistical tensors.

(5) Transform back to the laboratory system and we end up with

$$\rho_q^{\lambda}(t) = \Sigma_{q'\lambda'} G_{qq'}^{\lambda\lambda'}(t) \rho_{q'}^{\lambda'}(0).$$

The time-dependence of the density matrix is given by the equation of motion.

$$i\bar{h}\rho(t) = [H, \rho]$$

We consider only time-independent Hamiltonians so

$$\rho(t) = e^{-iHt/\bar{h}} \rho(0) e^{iHt/\bar{h}} \qquad \text{(II.14)}$$

We also use the formulas II.1,2,3.

$$\rho_{q'}^{\lambda'}(t) = \Sigma_{q''} (\rho')_{q''}^{\lambda'}(t) D_{q''q'}^{\lambda'}(\Omega)$$

$$= \Sigma_{q''m}(I=m\ I\ m'|\lambda' q'')(-1)^{\lambda'-I-m}$$

$$<I\ m|\rho'(t)|I\ m'> D_{q''q'}^{\lambda'}(\Omega)$$

$$= \Sigma_{q''m''m'''} (I-m\ I\ m'|\lambda'\ q'')$$

$$(-1)^{\lambda'-I-m} D_{q''q'}^{\lambda'}(\Omega) x$$

$$x<I\ m|\ e^{-iHt/h}|I\ m''><I\ m''|\rho'(0)|I\ m'''>\ x$$

$$x\ <I\ m''\ '|e^{iHt/\bar{h}}|I\ m'>$$

$$= \Sigma_{q''mm'''m'''\,'\lambda}(I\text{-}m\ I\ m'\,|\lambda'\ q'')\ x$$

$$x\ (-1)^{\lambda-I-m}\ D^{\lambda'}_{q'',q'}(\Omega)x$$

$$x\ \langle I\ m|\ e^{-iHt/\bar{h}}\ |I\ m''\rangle\langle Im'''|e^{iHt/\bar{h}}\ |I\ m'\rangle\ x$$

$$x\ (\rho')^{\lambda}_{q'',\,'}(0)\ (I\ -m''\ \ I\ m''\,'\,|\lambda\ q''\,')(-1)^{\lambda-I-m''}$$

$$= \Sigma_{q''qmm''m''\,'\lambda}(I\text{-}m\ I\ m'\ |\lambda'\ q'')(-1)^{\lambda+\lambda-2I-m-m''}\ x$$

$$x\ \langle I\ m|e^{-iHt/\bar{h}}\ |I\ m''\rangle\ \langle I\ m''\,'|\ e^{iHt/\bar{h}}\ |I\ m'\rangle\ x$$

$$x\ (I\ -m''\ \ I\ m''\,'|\lambda\ q''\,')\ \rho^{\lambda}_{q}(0)\ D^{\lambda}_{qq'',\,'}(-\Omega)\ D^{\lambda'}_{q'',q'}(\Omega)$$

$$\equiv \Sigma_{\lambda q}\ G^{\lambda\lambda'}_{qq'}(t,\Omega)\ \rho^{\lambda}_{q}(0) \qquad \text{(II.15)}$$

This is the general expression for the pertubation coefficient due to a static Hamiltonian. It is applicable in all cases of geometry.

There are a couple of experimental conditions, which can reduce this expression to more workable formulae.

(a) The 'creation' system, in which ρ is cylindrically symmetric, coincides with the laboratory system. That means $\rho^{\lambda}_{q}(0) = 0$ for $q \neq 0$.

So

$$\rho^{\lambda'}_{q'}(t) = \Sigma_{\lambda}\ G^{\lambda\lambda'}_{oq'}(t)\ \rho^{\lambda}_{o}(0) \qquad \text{(II.16)}$$

(b) A random orientation of the crystal systems with respect to the laboratory system, as encountered in micro-cystalline samples. Then we can perform an integration over Ω.

$$\frac{1}{4\pi}\int D^{\lambda}_{oq'',\,'}(-\Omega)\,D_{q''q'}(\Omega)\,d\Omega =$$

$$\frac{1}{4\pi}\int D^{*\lambda}_{q''\,'\,'o}(\Omega)\,D_{q''q'}(\Omega)\,d\Omega = \frac{1}{2\lambda+1}\,\delta_{q''\,'q''}\,\delta_{q'o}\,\delta_{\lambda\lambda'} \qquad \text{(II.17)}$$

Here we can integrate over two angles α and β, for γ may be taken zero and still we will describe the rotation. When we are averaging over the total solid angle the factor 4π drops out. Substitute (II.17) and (II.16) in (II.15)

$$\rho^{\lambda}_{o}(t) = \Sigma_{q''mm''}\,(I\ -m\ I\ m'|\lambda\ q'')(-1)^{2\lambda\ -\ 2I\ -\ m\ -\ m''}\ x$$

$$x\ \langle I\ m|\ e^{-iHt/\hbar}\ |I\ m''\rangle\langle I\ m''\ '|\ e^{iHt/\hbar}\ |I\ m'\rangle\ x$$

$$(I\ -m''\ I\ m'''|\lambda\ q'')\ \rho^{\lambda}_{o}(0)\ \frac{1}{2\lambda+1} \qquad \text{(II.18)}$$

(c) The interaction Hamiltonian is diagonal in $|I\ m\rangle$

$$\langle I\ m|\ e^{-iHt/\hbar}\ |I\ m''\rangle = e^{iHt/\hbar}\ \delta_{mm''}$$

This substituting in (II.18)

$$\rho_o^{\lambda}(t) = \Sigma_{q'',m}(I\ -m\ I\ m'|\lambda\ q'')(-1)^{2\lambda-2I\ -2m}\ e^{-iE_m t/\bar{h}}\ x$$

$$x\ e^{iE_{m'}t/\bar{h}}\ (I\ -m\ I\ m'|\lambda\ q'')\ \rho_o^{\lambda}(0)\ \frac{1}{2\lambda\ +\ 1}$$

$$= \Sigma_{q'',m}(I\ -m\ I\ m'|\ q'')^2 \cos\{(E_m\ -\ E_{m'})t/\bar{h}\}\ \rho_o^{\lambda}(0)$$

(II.19)

$(-1)^{2\lambda-2I-2m} = 1$ for the exponent is always even.

$(E_m - E_{m'}) = -(E_{m'} - E_m)$ so the sine functions will cancel each other and we are left with the cosines.

Formula (II.19) is the often derived formula useful for an axially symmetric quadrupole interaction, measured in a microcrystalline sample. For a magnetic field $(E_m - E_{m'})$ is a constant for the allowed transitions of $\Delta m = \pm 1$, and this will further reduce the expression.

For a Hamiltonian, which is not diagonal in the $|I\ m\rangle$ representation, we have to diagonalize it to a set of eigenvectors $|n\rangle$. The transformation from $|I\ m\rangle$ to $|n\rangle$ is described by the transformation matrix U. U is unitary and $U^{-1}U = 1$.

$$\Sigma_{mm'} \langle m|\ H\ |m'\rangle =$$

$$\Sigma_{mm'} \langle m|\ U^{-1}U\ H\ U^{-1}U\ |m'\rangle =$$

$$\Sigma_{m''m''' nn' mm'} \langle m''|n\rangle \langle m''|m'''\rangle \langle n|\ H\ |n'\rangle\langle m'''|m''''\rangle\langle n'|m'\rangle =$$

$$\Sigma_{mm'\,n}\; U_{mn}\; E_n\; \delta_{nn'}\; U^{-1}_{n'm'} \;=$$

$$\Sigma_{mm'n}\, U_{mn}\, E_n\, \delta_{nn'}\, U^{*}_{m'n}$$

Use in (II.18)

$$\rho_o^{\lambda}(t) = \Sigma_{q''mm''nn'}\, (I\ -m\ I\ m'|\lambda\ q'')\ (-1)^{2\lambda\ -\ 2I\ -\ m\ -m''}\ x$$

$$x U_{mn}\, U^{*}_{m''n}\, e^{-iE_n t/h}\, U_{m''\ 'n'}\, U^{*}_{m'n'}\, e^{iE_{n'} t/h}\ x$$

$$x(I\ -m''\ I\ m''\ '|\lambda\ q'')\ \rho_o^{\lambda}(0)\ \frac{1}{2\lambda\ +\ 1} \qquad \text{(II.20)}$$

This is the formula for the perturbed angular distribution for a non-axially symmetric Hamiltonian, from a cylindrically symmetric state at time zero in a microcrystalline sample. As is evident the pertubation factor $G(t) = \rho(t)/\ \rho(0)$ is only dependent on the multipolarity of the γ-decay and the Hamiltonian.

II.3 The Hamiltonian for Quadrupole Interaction

The electrostatic Hamiltonian of a charge distribution in an external field is (De53)

$$H_{el} = \int \rho(\vec{x})\ V\ (\vec{x})\ d^3x$$

Where $\rho(\vec{x})$ the local charge density is.

A Taylor expansion of the potential about the origin is

$$V(x) = V(0) + \vec{x}.\vec{\nabla}V(0) + \tfrac{1}{2}\,\Sigma_i\ \Sigma_j\ \frac{\partial^2 V}{\partial x_i \partial x_j}\ (0)\ x_i x_j + \ldots\ldots$$

$$\text{So} \qquad H_{el} = \int \rho(\vec{x})\, V(0)\, d^3x +$$

$$+ \int \rho(\vec{x})\, \vec{x}.\, \vec{\nabla} V(0)\, d^3x +$$

$$+ \int \rho(\vec{x})\, \Sigma_{ij}\, x_i x_j\, \frac{\partial^2 V}{\partial x_i \partial x_j}\,(0)\, d^3x + \ldots\ldots \qquad \text{(II.21)}$$

The first term is the energy of the nucleus in its surroundings and not important for this problem. The second term vanishes because the nucleus is in a minimum of the potential so $\vec{\nabla}\, V = 0$. The third tem is the quadrupole interaction, the higher order terms are neglected. We can write the quadrupole interaction as

$$H = \tfrac{1}{2}\, \Sigma_{ij}\, T^{(2)}_{ij}\, V^{(2)}_{ij} \qquad \text{(II.22)}$$

where $T^{(2)}$ is the second-rank tensor, the quadrupole moment tensor, and $T_{ij} = \int \rho(\vec{x})\, x_i x_j\, d^3x$ and $V^{(2)}_{ji} = \frac{\partial^2 V}{\partial x_i \partial x_j}\,(0)$ is the component of the field gradient tensor.

It is always possible to make the field gradient tensor diagonal by a suitable choice of the coordinate system. Furthermore the Laplace equation is valid for V describes only the external field.

$$V_{xx} + V_{yy} + V_{zz} = 0 \qquad \text{(II.23)}$$

By defining the axis properly the usual condition is

$$|V_{zz}| \geq |V_{yy}| \geq |V_{xx}| \qquad \text{(II.24)}$$

Define $\eta = (V_{xx} - V_{yy})/V_{zz}$ (II.25)

From (II.23) and (II.24) it follows that $0 \leq \eta \leq 1$. In this way the field gradient is described by V_{zz} and η and the orientation of the coordinate system.

$T^{(2)}$ and $V^{(2)}$ can be expanded in spherical tensors

$$T^{(2)} = \Sigma_{q=-2}^{+2} T_q^2 \quad \text{and}$$

$$V^{(2)} = \Sigma_q V_q^2 \ .$$

So $$H = \tfrac{1}{2} \Sigma_q T_q^2 V_{-q}^2 \ .$$

For a diagonal field tensor

$$V_{\pm 1}^2 = 0$$

$$V_0^2 = V_{zz} \qquad \text{(II.26)}$$

$$V_{\pm 2}^2 = \frac{1}{\sqrt{6}} (V_{xx} - V_{yy}) = \frac{1}{\sqrt{6}} \eta V_{zz}$$

$$\langle I\ m|\ H\ |I\ m'\rangle =$$

$$\langle I\ m|\tfrac{1}{2} \Sigma_q T_q^2 V_{-q}^2\ |I\ m'\rangle =$$

$$\tfrac{1}{2} \Sigma_q V_{-q}^2 \langle I\ m|\ T_q^2\ |I\ m'\rangle =$$

$$\tfrac{1}{2} \Sigma_q (-1)^4 \langle I||\ T^{(2)}\ ||I\rangle V_{-q}^2 (I\ m'\ 2\ q|I\ m)$$

The quadrupole moment of the nucleus is defined as

$$eQ \equiv \int \rho_n (r^2 - z^2)\, d^3x$$

$$= 2 \int \rho_n \, x^2 \, d^3x$$

$$= 2 \langle II | \, T_0^2 \, | II \rangle$$

$$= 2 \, (-1)^4 \, (I \; I \; 2 \; 0 | I \; I) \langle I \, || \, T^{(2)} \, || I \rangle$$

So $\langle I \; m | \, H \, | I \; m' \rangle =$

$$\tfrac{1}{4} \, \Sigma_q \, eQ \, (I \; m' \; 2 \; q | I \; m) \, (I \; I \; 2 \; 0 | I \; I)^{-1} \, V_{-q}^2$$

Calculate the Clebsch-Gordan coefficients and substitute the values for the components of V

$$q = 0 \quad \langle I \; m | \, H \, | I \; m' \rangle = (3m^2 - I(I+1)) \, \frac{eQ}{4I(2I-1)} \, V_{zz} \, \delta_{mm'}$$

$$q = \pm 1 \quad \langle I \; m | \, H \, | I \; m' \rangle = 0 \qquad \text{(II.27)}$$

$$q = \pm 2 \quad \langle I \; m | \, H \, | I \; m \mp 2 \rangle =$$

$$\{(I \mp m - 1)(I \mp m)(I \pm m + 1)(I \pm m + 2)\}^{\frac{1}{2}} \, \frac{eQ}{4I(2I-1)} \, \frac{\eta}{\sqrt{6}} \, V_{zz}$$

These values are also derived by Matthias, Schneider and Steffen (Ma62 and Ma63) using the expansion of the Coulomb potential in spherical harmonics. It should be noted that the definitions in this reference for both T and V differ a constant factor from the definition used above.

CHAPTER III

EQUIPMENT

Beam

We used the 7 MeV Van de Graaff accelerator of the University of Alberta, with a pulsed beam of 1 ns width with a repetition rate of 1 MHz.

Detectors

As detectors we used 4 Ge(Li) detectors, 2 in each experiment, with volumes of 20.7, 23.0 and 27.4 cc and the LEPS detector. The three large detectors combine good energy resolution with good time resolution and a wide efficiency range. The LEPS detector (3 cc) is very good for low energies (less than 400 KeV) and less sensitive to higher energy γ-rays reducing the counting-rate by a large factor.

Electronics

We had two electronic setups, one for two time dependent measurements at one time and one for one timing and one monitor. The double timing had the drawback that the tuning was more complicated and that the sum boxes were not able to handle high counting rates. The single timing cost more time, but was easy to set up, and could handle high counting rates. The time-resolution of the system was typically 2.7 ns FWHM for 843 keV and 8.0 ns for 188 keV.



Fig 2: The electronic arrangement with two timing counters





Fig 3: The electronic arrangement with the single timing counter and the monitor counter

A major problem which showed up was the appearance of 10 and 30 MHz ripples in phase with the 1 MHz beam pick-off. This showed up in the time spectra as a modulation of the yield as function of the time. We suppressed it partly with a 50 ns delayed reflection, gaining at least a factor 4.

For the timer we used a time-to-amplitude converter (TAC), supplied with a start-signal from the Ge(Li) detector. The stopping side was from the beam pick-off. This signal was delayed to place the prompt peak on the end of the spectrum. This set-up had the effect that there was always a stop-signal and that the time in our time spectrum was running backwards.

The calibration was performed with a commercial calibrator (Ortec model 462). For on-line sorting of data we used the program TWO PARAMETER SORTING, available on the Honeywell 516 computer. For description see Chapter IV.

Target Mounting

(1) Normal beamstop target. In the figure 4 are also indicated the other devices, i.e. pulse pick-off which gives the time-signal from the beam, the energy slits and the collimator, together with the definition of θ_γ. The other target holder assemblies replace that shown to the right of the dotted line in Figure 4. The collimator is not shown in the next figures

(2) Hot target chamber. For heating up experiments we designed a target chamber with a heating system and control



Fig 4: The normal beam stop target holder with surrounding devices

unit. After some trials this final set-up had these properties:

(a) Ceramics were high temperature castable ceramics from Aramco.

(b) The target holder can be placed at an angle up to 30° to the beam, made possible with a rotatable connection above the heating-wire.

(c) The target holder, the heating wire and the nickel hat, which served as a Faraday cup and as a shielding of the surroundings, were electrically isolated to the ground and each other.

(d) The obtainable temperature was at least 600 K.

(e) The required power input for 560 K was approximately 35 Watt.

(f) The temperature was stable within 0.1 K, for each temperature, if the beam was constant. Large fluctuations of the beam resulted in the temporary change in temperature. Too much power input resulted in large temperature variations.

(g) Due to the heat input from the beam the temperature of the centre of the target was 70 - 100 K above the measured temperature. This is calculated in Appendix I and verified with the sublimation rate of natural zinc. All quoted temperatures are 85 K above the measured temperatures.

(h) The thermocouple was a standard Fe/Constantan thermocouple. The results were interpreted with



Fig 5: Hot target chamber. The 5 feedthroughs are for the heating-wire (2) the thermocouple (2) and the current collector



Fig 6: The control box circuit diagram. This circuit switches the power on or off if the reading of the thermocouple is lower or higher than required



Fig 7: The calibration of the controlbox as function of the reading of the thermocouple

the tables in the Handbook of Chemistry and Physics (Ha72).

(3) Background surpressing target holder. For the ^{18}F experiments we encountered a high 511 keV γ-yield from the annihilation of the β^+ of the ^{18}F decay. Using the fact that the half-life is 110 min, we shielded in this set-up four targets with 2 cm lead and used the fifth target for the measurements. By changing the targets every 30 min. we were able to reduce the compton background from the 511 keV γ ray in the region of interest, 180 - 200 keV, by a factor 3 to 4 relative to the yield of the 188 keV ^{18}F γ ray. The ladder with the five targets can slide in and out without disrupting the vacuum. The targets are electrically isolated from the chamber.



Fig. 8: The background suppressing target holder.

CHAPTER IV

DATA ANALYSIS

As described in Chapter III the electronics give to the Honeywell 516 computer 3 signals, an analog time-signal, an analog energy-signal and a logic 'event'-pulse. The event-pulse serves the purpose, that during the pulse the computer accepts both other pulses and processes them according to the program. ADC's convert both other signals from analog to digital with up to 4096 channels after which the program TWOP stores both in a separate memory region and if the energy happens to fall in one of the set regions in the energy spectrum, the so-called windows, its corresponding time is also stored in a third memory region. So we have three spectra, the energy, the times of all γ ray's and the times of γ ray's with certain energies, for each window one complete time-spectrum. After each run the data was written on magnetic tape for off-line analysis on the XDS 940.

The off-line analysis is with the program TDPAD (Lu75) especially developed for the analysis of these experiments. It is able to fit time spectra and background of the peak of interest to the time-dependent angular distribution coefficients and fits that to the theoretical curve which depends on the frequency, its relative spread, the spin, the asymmetry parameter η, the unperturbed value of a_2 and a_4, the $A_0(t)$ and the interaction

frequency $\omega_q = (e^2Qq)/\bar{h}$.

The TDPAD-program is essentially fitting to the formulae (II.11) and (II.20), using the Hamiltonian given by (II.27). The pertubation-coefficient as described is

$$G_k(t) = \Sigma_N s_{kN} \cos (N\omega_q t) \qquad (IV.1)$$

For the axially-symmetric case N is integer, but deviates in general from integral values for $\eta \neq 0$. The s_{kN} are easily obtainable from (II.20),

$$N \equiv (E_n - E_{n'})/(\bar{h}\omega_q) \text{ and } \omega_q = (e^2Qq)/\bar{h}.$$

Because all nuclei do not feel the same field gradient, due to slight displacements in the microcrystals, we have a relative frequency spread $\delta\omega$. We assume the Lorentzian frequency distribution given in (Ha73).

$$G_k'(t) = \Sigma_N s_{kN} e^{-N\omega_q \delta\omega t} \cos N\omega_q t \qquad (IV.2)$$

Both (IV.1) and (IV.2) are the theoretical curves for infinite time resolution. This is experimentally unobtainable, so we have to take into account the time resolution of the system. This is a Gaussian distribution and can be described by

$$G_k''(t) = \Sigma_N s_{kN} e^{-N\omega_q \delta\omega t} e^{(N\omega_q \tau)^2/2} (\cos N\omega_q t) \qquad (IV.3)$$

where τ is the time resolution.

The fit is to

$a_k(t) = a_k(0)\, G_k''(t) + c$, where c is a time-independent constant. $G_k(t)$ is calculated by numerically diagonalizing of the Hamiltonian.

The theoretical curves, as they are calcualted with the formulas (IV.1), (IV.2) and (IV.3) are shown in the figures, for a couple of typical spins and spins of interest, with various asymmetry parameters, resolution times and frequency spreads.

In the literature ω_o is often given instead of ω_q is noted. ω_o is defined as the smallest energy-difference for an axially symmetric field

$$\omega_o = \frac{3}{4I(2I-1)}\ \omega_q \qquad \text{for integer spin}$$

$$\omega_o = \frac{6}{4I(2I-1)}\ \omega_q \qquad \text{for half-integer spin.}$$

We prefer to use ω_q for it is dependent only on the interaction parameters Q and q and not on the spin.

Figures 9 - 18:

The values of the $G_2(t)$ term as function of time for different values of spin, η, $\delta\omega$ and resolution time τ. Note that Fig. 9 is the $G_4(t)$ curve for spin 2. For all curves the first case is represented by the solid curve, the second by the dashed and the third by the dash dot line.



Fig 9: Spin = 2 η = 0.0,0.5,1.0 $\delta\omega$ = 0.0 τ = 0.0 The $G_4(t)$ term



Fig 10: Spin 2 η = 0.0,0.5,1.0 $\delta\omega$ = 0.0 τ = 0.0 The $G_2(t)$ term





Fig. 11: Spin = 3 η = 0.0,0.5,1.0 $\delta\omega$ = 0.0 τ = 0.0



Fig. 12: Spin = 5/2 η = 0.0,0.5,1.0 $\delta\omega$ = 0.0 τ = 0.0



Fig 13: Spin = 4 η = 0.0,0.5,1.0 $\delta\omega$ = 0.0 τ = 0.0



Fig 14: Spin = 5 η = 0.0,0.5,1.0 $\delta\omega$ = 0.0 τ = 0.0



Fig 15: Spin = 4 η = 0.4 $\delta\omega$ = 0.0 τ = 0.0,1.0,2.5
Channels for ω = 5 rad/ch.



Fig 16: Spin = 4 η = 0.0 $\delta\omega$ = 0.0 τ = 0.0,1.0,2.5
Channels for ω = 5 rad/ch.



Fig 17: Spin = 4 η = 0.4 $\delta\omega$ = 0,2,5% τ = 0.0



Fig 18: Spin = 4 η = 0.0 $\delta\omega$ = 0,2,5% τ = 0.0

CHAPTER V

THE EXPERIMENTS

V.1 ^{70}Zn (p,n) ^{70}Ga

The experiment was initiated because a discrepancy existed between the spin assignment from particle work and the measured anisotropy in the γ decay of the 879 keV level, especially when compared with the 411 keV γ ray from the 1102 keV level, which also was assigned a spin 4 (Do72). Together with the life time and the possibility of an Electric Field Gradient, we extracted the unperturbed value of the anisotropy, to see if this is in agreement with the prediction.

The 879 keV level of ^{70}Ga has a half-life of 22.7 ns (Hu75) and decays to the 691 keV level ($I^{\pi} = 2^{-}$). Both the 188 keV and the 691 keV γ rays are suitable for doing a time-dependent measurement as long as one takes into account that the region of 188 keV is populated with much abundant γ's, i.e. 197 keV of ^{19}F, 191 keV of ^{197}Au, 185 keV of ^{64}Cu, 175 keV of ^{71}Ge and the backscattering edge of the Comptons of 511 keV. The 691 keV coincides with the 692 keV E0 transition in ^{72}Ge from (n,n') in the Ge(Li) detectors. Another drawback is the relatively short lifetime of the decay.



Fig. 19: The level scheme of ^{70}Ga with the transitions of interest.

Figure 20:

A typical γ - spectrum from ^{70}Zn (p,n) ^{70}Ga. The labels are the energies in keV.


counts
100000
20000
440
282
197
188
159
319
344
364
411
42


counts
100000
20000
475
508
511
584
631
651
691
770
43

In developing a hot-target chamber the aluminum has to be shielded for this gives too much background radiation. The target should also be prevented from evaporating. The use of mica for this purpose is unacceptable for it gives too much annihilation radiation. The solution was found in clamping two .0003" thick nickel foils around the target.

The target was a 1.9 mg/cm^2 foil of enriched ^{70}Zn (68%). The beam was 2.85 or 2.9 MeV protons, which is 300 keV above the threshold for the 879 keV level, and the nuclei are aligned by the reaction. There were three measurements done in a single run, one at 410 K, one at 420 K and one at 510 K. We used the double-timing system and measured only two angles, 0° and 90°. This has the problem that the a_2 term is determined only when a_4 term is negligible.

A run at 560 K and one at 340 K, were performed using the single timing set-up and at five angles each.

We fitted the data with a normalization to the 651 keV line, assuming that the time-integrated yield of this decay is isotropic (Do72). The time zero is defined by the position of the background prompt peak in the time-spectrum, fitted with peakfit program. The time resolution was measured with a prompt peak in the region of interest.

When the data were analyzed with an infinite time-resolution, they yield results published in Nucl. Physics (Hu75), and reproduced in Table 1. These values have one feature which makes them unbelievable, the high frequency

Table 1

UNPERTURBED VALUES OF LEGENDRE POLYNOMIAL COEFFICIENTS

(THE FIT IS DONE WITHOUT TIME RESOLUTION)

Target Temperature	E_p(MeV)	Transition 879 → 691 a_2	879 → 691 a_4	691 → 0 a_2	691 → 0 a_4	ω_q (MHz)	$\frac{\delta\omega}{\omega_q}$ (%)	X^2/n
300 K	2.85	0.51±0.03	-0.35±0.04	-0.30±0.02	0.05±0.05			
						340	24	0.99
	3.40	0.31±0.02	-0.10±0.03	-0.22±0.01	0.05±0.03			
560 K	2.85	0.43±0.01	-0.26±0.02	-0.33±0.02	0.03±0.03	298	40	1.47

spread. When we introduce the finite time resolution and the asymmetric field gradient, it turns out that the time resolution pushes the frequency spread down to zero.

Out of the analysis it followed that one cannot distinguish clearly between the various spins. Neither spin 3 nor spin 5 can be excluded for the 879 keV level with these experiments. This is caused by the short life time compared to the full period of the time-dependence. Only the first recovery of the anisotropy is seen and this is not sufficient to determine the spin. Only spin 3, 4, 5 were considered for the others are excluded on the basis of spin assignments from particle reactions. All the values calculated below are for spin 4. If spin 3 or 5 is chosen for the level, one must scale these values. When the recovery is set at a fixed time, ω_o will be different for the three cases. Then $\omega_o = 3\omega_q/(4I(2I-1))$, so ω_q is certainly different for the three cases.

TABLE 2

SCALING FACTORS FOR ω FOR DIFFERENT SPINS

Spin	ω_o	ω_q
3	1.520	0.814
4	1.000	1.000
5	0.847	1.361

(η = 0, values normalized to spin 4)

This is confirmed with the analysis of the data with the three different spin values.

Neither is the value of η determined. For spin 4 the value of η is restricted to $0.0 \leq \eta \leq 0.6$. This large range is also due to the small part of the full cycle which is visible.

All values of a_2 and a_4 can be affected by a misalignment of the set-up up to 0.05. This error is not quoted in the table, but is common to the 188 and the 691, and will appear in the constant term c, which is a time-independent constant added to $a_k G_k(t)$ to get "$a'_k(t)$". This constant term absorbs also the normalization errors.

All data or typical samples of it are shown in the table and figures. The a_4 of the 691 γ ray is consistent with 0.00 and not quoted in the table.

V.2 The ^{18}F Trial

We tried to measure the quadrupole moment of the 1121 keV level of ^{18}F, which decays with a 184 keV γ ray to the 937 keV level, which subsequently decays to the ground state. The 1121 keV level has a spin 5^- and a half-life of 145 ns.

Since fluorine doesn't have a simple non-cubic crystal in any of its compounds, we wanted to compare ^{18}F with the 197 keV level in ^{19}F, which has a known Quadrupole moment. Radiation damage, which is dependent on the beam intensity and energy, can change the effective E.F.G.. So we wanted to

Table 3

THE DATA FROM THE VARIOUS RUNS FOR ^{70}Ga

T(K)	ω_q(MHz)	X^2	Nf	C	$a_2(0)$	$a_2'(0)$
188 keV ray						
560	330	63.7	34	0.04	0.278 ± 0.008	0.32 ± 0.01
510	316	41.5	25	0.13	0.255 ± 0.026	0.38 ± 0.03
420	315	28.2	25	0.17	0.264 ± 0.021	0.43 ± 0.02
410	316	28.7	25	0.17	0.209 ± 0.020	0.38 ± 0.02
340	319	19.5	24	0.08	0.341 ± 0.022	0.42 ± 0.02
691 KeV ray						
560	330	25.6	23	-0.13	-0.156 ± 0.017	-0.29 ± 0.02
510	316	37.4	26	-0.06	-0.169 ± 0.020	-0.23 ± 0.02
420	315	32.9	26	-0.05	-0.170 ± 0.018	-0.22 ± 0.02
410	316	17.6	26	-0.03	-0.186 ± 0.020	-0.22 ± 0.02
340	319	14.7	22	-0.025	-0.257 ± 0.022	-0.29 ± 0.02
188 KeV ray						
					$a_4(0)$	$a_4'(0)$
560	330	41.2	34	-0.04	-0.051 ± 0.014	-0.09 ± 0.02
340	319	12.1	24	0.00	-0.144 ± 0.050	-0.14 ± 0.05

Nf is the number of degrees of freedom in fitting a(t) to the theory

$$a'(0) = a(0) + C$$

Time-integrated values for the 188 keV transition.

Temperature	a_2	a_4
340 K	0.20 ± 0.01	-0.11 ± 0.02
560 K	0.21 ± 0.01	-0.06 ± 0.02

Fig. 21-34: The experimental results of ^{70}Ga in Zinc at various temperatures.


$a_4 G_4(t)$
0.2
0
-0.2
40
80
120
η
0.0
0.2
0.4
340 K 188 keV
$a_2 G_2(t)$
0.4
0.2
0
20
40
60
80
100
120
t (ns)
η
0.4
0.2
0.0
340 K 188 keV


$a_4 G_4(t)$
0.2
0
-0.2
40
80
140
t(ns)
340 K 691 keV


$a_2 G_2(t)$
0.2
0
-0.2
20
60
80
t(ns)
0.0
0.2
0.4
340 K 691 keV




$a_2G_2(t)$
0.2
0
-0.2
20
40
60
t(ns)
410 K 691 keV


$a_2G_2(t)$
0.6
0.4
0.2
0
20
40
60
80
100
t(ns)
410 K 188 keV




$a_2G_2(t)$
0.2
0
-0.2
20
40
t(ns)
420 K 691 keV


$a_2G_2(t)$
0.6
0.4
0.2
0
20
40
60
80
100
t(ns)
420 K 188 keV




$a_2G_2(t)$
0.2
0
-0.2
20
40
60
t(ns)
510 K 691 keV


$a_2G_2(t)$
0.6
0.4
0.2
0
20
40
60
80
120
t(ns)
510 K 188 keV


$a_4G_4(t)$
0.2
0
-0.2
20
40
60
t(ns)
560 K 188 keV


$a_2G_2(t)$
0.4
0.2
0
20
40
60
100
t(ns)
560 K 188 keV


$a_4 G_4(t)$
0.2
0
-0.2
20
40
t(ns)
560 K 691 keV


$a_2 G_2(t)$
0.2
0
-0.2
20
40
60
80
120
t(ns)
560 K 691 keV



measure both frequencies in the same run, to ensure that both E.F.G. are the same.

We used the reactions ^{16}O (^{3}He,p) ^{18}F and ^{19}F (^{3}He,^{3}He) $^{19}F^{*}$ with 2.95 MeV ^{3}He beam. The target was an oxide with a layer CaF_2 evaporated on it. The present recoil energy required a thickness of CaF_2 less than 100 $\mu g/cm^2$. We measured the thickness of a sample with α particle back-scattering and used the yield of the 197 keV γ ray of this sample as calibration. In this way one is able to tell if the targets are thin enough. 5 targets are less than 100 $\mu g/cm^2$ in thickness. The choice of the oxide is bound by some conditions. The anion in the oxide should not give a lot of radiation in the 3 MeV ^{3}He beam. This excludes Si and lower Z materials, for most of them yield β^{+}-unstable nuclei, producing too many annihilation γ rays and their comptons. Secondly the oxide should be non-cubic, preferably hexagonal, rhombic or tetragonal. We found the solution in V_2O_5 molten on a tantalum backing, with CaF_2 evaporated on top.

The ^{18}F annihilation peak produced that much back-ground in the 180 - 200 keV region, that a background surpress-ing target chamber had to be designed using the fact that the half-life of ^{18}F is 110 min. One target was used for 30 min. then shielded for the detectors while measuring on the other targets. This way one is able to reduce the background at 184 keV by a factor 3 to 4.

V.3 ^{69}Ga (d,p) ^{70}Ga

With this experiment we start to get some comparison between gallium ions in Zn and Ga metallic surroundings. This already has been done with Ge as probe (Ha73a). We used natural Ga and excited the 879 keV level with 5.5 MeV deuterons. The only experimental difficulty was the low melting point of gallium metal which is only 29.8 °C. The target was cooled by using the background surpressing target chamber and immersing the rod of the target ladder into ice water. Probably due to poor thermal contact between the target and the ladder we didn't succeed in maintaining our target solid, and measured so the time differential pattern of ^{70}Ga in liquid Gallium. The results show the feasibility of studying the quadrupole interaction of ^{70}Ga with the (d,p) reaction. The unperturbed value of a_2 is approximately 0.1.

CHAPTER VI

DISCUSSION OF THE RESULTS

VI.1 The Frequencies

The frequencies quoted in Table 3 have an uncertainty of 3%, in which region the X^2 changes by only up to 3% of the quoted minimal value. A change in the frequency will slightly affect the unperturbed a_k values.

The values with their uncertainties are plotted in Fig. 35 as function of the temperature. From this graph follows the value of ω_q at 300 K of (315 ± 10) MHz. The change in frequency from 300 K to 600 K is (+3 ± 6)%.

A definite calculation of the E.F.G. has not yet been performed. According to the current theory

$$eq = (1 - \gamma_\infty)eq_{lat} + (1 - R)eq_{loc} \qquad (VI.1)$$

where q_{loc} is due to the electrons in a shell around the nucleus not containing other ions,

q_{lat} is due to the other ions in the lattice and the electrons outside the shell.

γ_∞ represents the effect of the displacement of the core electrons in the lattice electric field. It is called the Sternheimer anti-shielding factor.



Fig 35: The dependence of ω_q on the temperature of ^{70}Ga in Zn



R is the shielding factor, which expresses the change in the E.F.G. of the electrons at the nuclear site due to the interaction of the nuclear quadrupole moment on the core electrons (Wa65 and refs. therein).

q_{lat} can be calculated for various lattices (We61 and Da61), yielding for our hexagonal Zn lattice $eq_{lat} = -1.5 \times 10^{16}$ V/cm^2. γ_∞, the anti-shielding factor has been also calculated and is -9.905 for ^{70}Ga. So $eq_{lat}(1 - \gamma_\infty) = -1.63 \times 10^{17}$ V/cm^2. The factor R is calculated by Sternheimer for various ions and determined to be 0.1 to 0.4 (St63 and refs. therein), but calculations of q_{loc} have not yet been performed adequately for most ions.

For an estimate of the local contribution of the E.F.G. the value from the graph in (Ra75) Fig. 36 was taken. This gives $(1 - R)eq_{loc} = +5.8 \times 10^{17}$ V/cm^2. So one estimates $eq = 4.1 \times 10^{17}$ V/cm^2, yielding with $\omega_q = 315$ MHZ $|Q| = 0.5$ barn.

The temperature dependence of ^{70}Ga in Zn deviates certainly less from the temperature dependence of q_{lat} than the various other ions in Zn (Fig. 37); this might indicate that the lattice contribution is in comparison larger than in the other cases. This would increase the magnitude of the quadrupole moment.

The other part, the calculated value of Q is not established. In appendix II the results are quoted for the



Fig. 36: Correlation of ionic and extraionic field-gradients in metals. Most values refer to room temperature. A typical temperature dependence is shown in the case of ZnCd by an arc of data points. Underlined symbols refer to the host metal. A and B refer to two inequivalent substitutional sites in ω-Zr. Filled circles indicate data from e^2qQ values of known signs. For open circles, e^2qQ signs are unknown. Locations of these points are predicted. (Ra75)



Fig. 37: The variation of the quadrupole frequencies of different ions in Zn with the temperature and the variation of the lattice part of the field gradient with the temperature.

calculation of the energy-levels in the Intermediate Coupling Model for ^{70}Ga. The results indicate that the results can be described with some admixing of phonon states. With the known quadrupole moment of the vibrational 2^+ state in ^{70}Ga of 0.38 b (Ch72) and the two particles outside the core, a quadrupole moment of 0.5 b is not unbelievable.

VI.2 The Anisotropy Coefficients

For a determination of the value of the anisotropy coefficient a_2 only the runs at 560 K and 340 K were taken into account. The three other runs are measurements with two angles only, which will easily introduce errors in the values large in comparison with the runs with 6 angles.

The experiments yield different values of a_2 for the various runs. This effect is not consistent between the 188 keV and the 691 keV γ rays, which indicates that misalignment is not the only effect. Various other authors (Be75, Va73, Bu74, Ha73) the same effect when studying the temperature dependence or pressure dependence of quadrupole interactions with the TDPAC technique. Two groups (Be74 and Ha73) report a reduction of the a_2 coefficient by a factor of two and more. All others show differences up to 25%.

Other γ rays of ^{70}Ga showed agreement between the two runs, and with the anisotropy coefficients as published by (Do72) and (Na73).

The theoretical expression for the time integrated attenuation coefficient is (Fr65)

$$\overline{G_k(\infty)} = \Sigma_N \, s_{kN} \, \frac{1}{1 + (N\omega_q\tau)^2} \qquad \text{(VI.2)}$$

where τ is the lifetime.

The values for this expression for halflife of 23 ns and spin 4 are plotted in Fig. 38., as a function of ω_q. For the 560 K run the value of the time integrated attenuation coefficient is 0.66 and the value of ω_q is 330 MH_z. For the 340 K run we have $\overline{G_2(\infty)}$ = 0.48 with ω_q = 319 MHz. If one compares these values with the curve it can be concluded that the 560 K run does not fit the theory of a static electric field gradient. The 340 K run does agree with the theory and it can be concluded that the $a_2(0)$ value is 0.42 ± 0.02 and $a_4(0)$ = 0.14 ± 0.05. For the 691 keV γ ray there is no possibility for such a check for the peak is obscured by the 692 KeV peak of ^{72}Ge.

The three other runs, which yield a mixture of a_2 and a_4, have consistent values for the coefficients of both transitions, but a temperature dependence is not excluded with the present error bars.

If a temperature dependence is present the results might be explained with the occurrence of a fraction, that does not take substitutional lattice sites, but experiences a time-dependent quadrupole interaction. This fraction will

Fig. 38: The time integrated attenuation coefficient as function of ω_q for a level with spin 4 and $t_{1/2}$ = 23 ns, for various values of η (0.0, 0.2, 0.4, 0.6, 0.8, 1.0, with 0.0 the highest values of $\overline{G_2(t)}$.


0.6
G_2
0.5
0.4
200
300
400
FREQ (MHz)

increase with increasing temperature. The time differential pattern of the anisotropy can be described with

$$G_2(t) = \Sigma_N s_{kN} e^{-N\delta\omega t} \qquad \text{(VI.3)}$$

where $\delta\omega$ is a large frequency spread as in formula (IV.2) (Be74a, Bo72, Va73). This might also explain the results of other results.

The constant c, which appears in the fitting will in these data absorb the effect of the non-substitutional fraction on the time dependent results. For the 340 K run it will probably not contain any effects of normalization errors, for these errors will have the same effect on the time integrated values as on the time differential results and the present values fit the theory for a static electric field gradient.

VI.3 General Conclusions

Despite experimental difficulties such as the short lifetime and a relatively small cross-section, these experiments yield the frequency and the unperturbed anisotropy coefficients, although not the spin and the η values.

The a_2 value of 0.42 ± 0.02 is in fair agreement with the value 0.38 predicted by the CN-model, (Hu75). It is also in agreement with the measured anisotropy of the 411 keV (Na73). The a_4 value of 0.14 ± 0.05 shows the same agreement as the a_2 value.

The ω_q value of 315 MHz is discussed in section VI.1 and indicate a quadrupole moment of 0.5 b, when it is assumed that the universal correlation of the components of the field gradient as suggested in Ra75 is true.

The TDPAD technique has the capability of measuring the quadrupole interaction, but has the drawback that it can only be performed with a pulsed beam. This gives us no possibility to place the nucleus in a particular place of a lattice TDPAC, which hasn't this drawback, has the disadvantage that the level of interest has to be fed by a long-lived parent ($t_{1/2}$ > 1 day). If these techniques are performed in combination with Mossbauer and NQR experiments, both of which have their own drawbacks, one is able to measure field gradients and quadrupole moments of most nuclei in various surroundings. But the difficulties in the measurements are clearly indicated by the fact, that the theory was well developed in 1962, and only in recent years have the experimental results been available in reasonable number.

REFERENCES

Be74 H. Bertschat, E. Recknagel, B. Spellmeyer. Phys. Rev. Lett. 32 (1974) 18.

Be74a H. Bertschat, H. Haas, F. Pleiter, E. Recknagel, E. Schlodder, B. Spellmeyer. Int. Conf. on Hyperfine Interactions studied in Nuclear Reactions and Decay. Conf. Uppsala 1974, p. 40.

Be75 H. C. Benski, J. Berthier, G. Teisseron, S. Choulet. Phys. Lett. 51A (1975), 467.

Bl72 J. Bleck, R. Butt, H. Haas, W. Ribbe, W. Zeitz, Phys. Rev. Lett. 29 (1972), 1371.

Bo72 E. Bodenstedt, U. Ortabasi, W. H. Ellis, Phys. Rev. B6 (1972), 2909.

Br62 D.M. Brink, G. R. Satchler, Angular Momentum (Oxford University Press 1962).

Br74 R. Brenn, G. Yue, G. D. Sprouse, O. Klepper, Int. Conf. on Hyperfine Interactions studied in Nuclear Reactions and Decay. Conf. Uppsala 1974, p. 206.

Bu74 T. Butz, G. Wortmann, G. M. Kalvius, W. B. Holsapfel, Phys. Lett. 50A (1974), 127.

Ch67 D. C. Choudhury, T. F. O'Dwyer, Nucl. Phys. A93 (1967) 300.

Ch72 A. Christy, O. Häusser, Nucl. Data Tables 11 (1972) 281.

Da61 T. P. Das, M. Pomerantz, Phys. Rev. 123 (1961) 2070.

De53 H. G. Dehmelt, Am. J. Phys. 22 (1953) 110.

Do72 D. A. Dohan, Thesis McMaster University (unpublished) 1972.

Fe69 F. D. Feiock, W. R. Johnson, Phys. Rev. 187 (1969) 39.

Fr65 H. Frauenfelder and R. M. Steffen in α, β and γ ray spectroscopy Vol. II ed. K. Siegbahn (North Holland Publishing Comp. 1965).

Ha72 Handbook of Chemistry and Physics (Chemical Rubber edition 1972).

Ha73 H. Haas, D. A. Shirley, J. Chem. Phys. 58 (1973) 3339.

Ha73a H. Haas, W. Leitz, H. E. Mahnke, W. Semmler, R. Sielemann, Th. Wichert, Phys. Rev. Lett. 30 (1973) 656.

Ha74 L. Hasselgren, F. Falk, B. S. Ghumman, C. Fahlander, J. E. Thun, Int. Conf. on Hyperfine Interactions studied in Nuclear Reactions and Decay, Uppsala 1974, p. 136.

Hu75 D. A. Hutcheon, D. M. Sheppard, P. Kitching, J. M. Davidson, C. W. Luursema, L. E. Carlson, Nucl. Phys. A245 (1975) 306.

Lu75 C. W. Luursema, D. A. Hutcheon, Internal Report Nucl. Research Centre U. of A. added as appendix III.

Ma62 E. Matthias, W. Schneider, R. Steffen, Phys. Rev. 125 (1962) 261.

Ma63 E. Matthias, W. Schneider, R. Steffen, Arkiv för Physik 24 (1963) 97.

Ma71 E. Matthias, B. Olsen, D. A. Shirley, J. E. Templeton, R. M. Steffen, Phys. Rev. A4 (1971) 1626.

Mc72 J. M. McDonald, P. M. S. Lesser, D. B. Fossan, Phys. Rev. Lett. 28 (1972) 1057.

Na73 M. R. Najam, L. E. Carlson, W. F. Davidson, W. M. Zuk Nucl. Phys. A211 (1973) 77.

Ra75 R. S. Raghavan, E. N. Kaufmann, P. Raghavan. Phys. Rev. Lett. 34 (1975) 1280.

Re74 R. C. Reno, R. L. Rasera, G. Schmidt. Phys. Lett. 50A (1974) 243.

Ro67 H. J. Rose, D. M. Brink, Rev. Mod. Phys. 39 (1967) 306.

St63 R. M. Sternheimer. Phys. Rev. 130 (1963) 1423.

Va73 A. Vasquez, J. D. Rogers, A. Maciel. Phys. Lett. 45A (1973) 253.

Wa65 R. E. Watson, A. C. Gossard, Y. Yafet. Phys. Rev. 140 (1965) A375.

We61 F. W. de Wette. Phys. Rev. 123 (1961) 103.

APPENDIX I

TARGET HEATING

When a beam deposit its energy O on the target, radius b and thickness d, in a circle with radius a (a < b) in the centre, the centre will have a higher temperature than the edge. The edge is assumed to absorb the heat without a temperature rise. The temperature as function of the radius is:

$$T(0) - T(r) = \frac{0}{4\pi dK} \{\frac{r}{a}\}^2 \qquad r \leq a$$

$$T(r) - T(a) = \frac{0}{2\pi dK} \ln \frac{r}{a} \qquad a \leq r \leq b$$

where K is the constant of thermal conductivity.

Define P = O/d, the energy loss of the beam per cm material. In this way

$$T(b) - T(0) = \frac{P}{4\pi K} \{1 + 2 \ln \frac{b}{a}\}.$$

Substitute the appropriate values for 3 MeV protons on a zinc target.

$$P = 70 \frac{keV}{mg/cm^2} \times 7200 \text{ mg/cm}^2 = 504 \text{ W cm}^{-1} \mu A^{-1}$$

$$K = 1.2 \text{ W / (cm K)}$$

for b/a = 3.0 ΔT = 106.9 K/μA

= 2.7 99.8

= 2.5 94.7

= 2.0 79.7

= 1.8 72.7

The sublimation rate of zinc, which was used as a check on the approximate temperature can easily be calculated. Every material has a vapor pressure, which will be pumped away in the high vacuum beam line. This pressure is given by

$$p_o = \frac{1}{3} \rho \overline{v^2}$$

where ρ is the density of the gas and v the velocity of the gas molecules. Per unit time the average distance travelled by the molecules is v_{av}. The mass escaping per unit time and per unit area is

$$\Delta m = 3 p_o v_{av} / \overline{v^2}$$

$$= p_o \sqrt{\frac{8m}{\pi kT}}$$

(For the formulae for v_{av} and $\overline{v^2}$ see ref. 1).

With the vapor pressure quoted in ref. 2 the sublimation rate of ^{70}Zn can be calculated and the values are tabulated in Table 4.

TABLE 4

SUBLIMATION RATE OF ZINC AS FUNCTION OF THE TEMPERATURE

T (K)	p_o (mm Hg)	Δ m ($\mu g/cm^2 s$)
421	10^{-10}	9.7×10^{-5}
449	10^{-9}	9.4×10^{-4}
481	10^{-8}	9.1×10^{-3}
517	10^{-7}	8.8×10^{-2}
559	10^{-6}	8.4×10^{-1}
611	10^{-5}	8.1×10^{0}

ref. 1 D. Halliday, R. Resnik, Physics (J. Wiley and Sons, N.Y., 1966)

ref. 2 American Institute of Physics Handbook, ed. D. E. Gray, 1972, p. 4 - 300.

APPENDIX II

THE LEVEL SCHEME OF ^{70}Ga IN THE INTERMEDIATE COUPLING MODEL

The Intermediate Coupling Model couples one or two particles in shell model states outside an even-even core to the vibrations of the core. The coupling is characterized by the energy of the phonons, the number of phonons and the coupling constant ξ (Ch67).

For ^{70}Ga the even-even core is ^{68}Zn. An estimate of the phonon energy of this nucleus is 1 MeV. The particle levels can be taken as the single-particle levels of ^{57}Ni and yield for the energies

$$E(|2p\ 3/2>) = 0.0\ \text{MeV}$$

$$E(|1f\ 5/2>) = 0.78\ \text{MeV}$$

$$E(|2p\ 1/2>) = 1.08\ \text{MeV}$$

$$E(|1g\ 9/2>) = 2.00\ \text{MeV}$$

except for the g 9/2 state, which is not observed in ^{57}Ni. The quoted value is the estimate of Dohan (Do72).

When the calculations are done with one phonon and 3 orbitals available for the proton and 2 orbitals for the neutron, the results predict a reasonable part of the observed level scheme. The other levels might have an admixture of two-phonon states.

The 4^- state at the calculated energy of 795 keV above the lowest state is built up as:

$$|4^-> = 0.977\,|0;\ p_{3/2}\ g_{9/2};\ 4> + 0.017\,|0;\ f_{5/2}\ g_{9/2};\ 4> +$$

$$-0.030\,|0;\ p_{1/2}\ g_{9/2};\ 4> - 0.140\,|1;\ p_{3/2}\ g_{9/2};\ 3> +$$

$$-0.084\,|1;\ p_{3/2}\ g_{9/2};\ 4> + 0.062\,|1;\ p_{3/2}\ g_{9/2};\ 5> +$$

$$-0.079\,|1;\ p_{3/2}\ g_{9/2};\ 6> - 0.028\,|1;\ f_{5/2}\ g_{9/2};\ 2> +$$

$$+0.024\,|1;\ f_{5/2}\ g_{9/2};\ 3> - 0.004\,|1;\ f_{5/2}\ g_{9/2};\ 4> +$$

$$-0.020\,|1;\ f_{5/2}\ g_{9/2};\ 5> + 0.034\,|1;\ f_{5/2}\ g_{9/2};\ 6> +$$

$$+0.042\,|1;\ p_{1/2}\ g_{9/2};\ 4> - 0.058\,|1;\ p_{1/2}\ g_{9/2};\ 5>$$

where $|1;\ f_{5/2}\ g_{9/2};\ 4>$ means a state with 1 phonon, the proton in the $f_{5/2}$ orbit, the neutron in the $g_{9/2}$ orbit and both particles coupled to spin 5.



Fig. 39: Comparison between the experimental and calculated level scheme for ^{70}Ga. The calculation is done with one phonon in the Intermediate Coupling Model.

APPENDIX III

INTERNAL REPORT #77

PROGRAM TDPAD

PROGRAM TDPAD

Nuclear Research Centre
University of Alberta
Edmonton, Alberta

INTERNAL REPORT #77

C.W. Luursema, and D.A. Hutcheon

Introduction

This program is meant for the analysis of a time dependent γ ray angular distribution due to static electric Quadrupole Interaction in randomly oriented microcrystals with the plane of detection containing the beam. It starts with time-delay spectra of the transition of interest and of background data for two or more angles and gives the least χ^2 fit parameters to the theoretical formula.

It is developed for the SDS, 940 for the Nuclear Research Centre, makes use of all 32K core and works only with Rad Monarch system.

TDPAD is a Fortran Linking program consisting out of three links. The three links 'Data', fitting the raw data to the anisotropy coefficients at various delay times, 'Display', fitting the coefficients to the theoretical expression and central processor and 'Sun' calculating the S_{kN} coefficients, are reasonably independent so the program doesn't switch very often during running.

It is assumed that the raw data, i.e. the yield as function of delay, are stored in maximal 1024 channels with the time running backwards, i.e. increasing channel number corresponds to decreasing delay.

Theory

Time dependent Perturbed Angular Distribution is given by (all refs.)

$$W(\Theta) = \Sigma_k (a_k G_k(t) + c) P_k(\cos\Theta)$$

where c is a time independent constant.

$$G_k(t) = \Sigma_{qmm''} \frac{1}{2k+1} (I\ -m\ I\ m'|k\ q)\ x$$

$$\Sigma_{nn'} (I\ -m''\ I\ m'''|k\ q)\ e^{-i(E_n - E_{n'})t/h}\ x$$

$$U_{mn}\ U^*_{m''n} U_{m'''n} U^*_{m'n'}$$

where U is the transformation matrix which diagonalizes the Hamiltonian ($UHU^{-1} = E$).

Since $(E_n - E_{n'}) = -(E_{n'} - E_n)$ we end up with only cosine terms

$$G_k(t) = \Sigma_N\ s_{kN} \cos N\omega t$$

where $\omega = e^2qQ/h$ and $N = \dfrac{(E_n - E_{n'})}{e^2qQ}$

The Hamiltonian is given by the elements

$$H_{m,m} = \frac{eQ}{4I(2I-1)} \left(3m^2 - I(I+1)\right) V_{zz}$$

$$H_{m,m\pm2} = \eta \frac{eQ}{4I(2I-1)}\ x$$

$$\{(I \mp m-1)\ (I \mp m)\ (I \pm m + 1)\ (I \pm m + 2)\}$$

with $V_{zz} = \dfrac{\partial^2}{\partial z^2} V$, evaluated at the nuclear site

and $\eta = \dfrac{V_{yy} - V_{xx}}{V_{zz}}$ and $0 \leq \eta \leq 1$

By taking into account a spread of frequencies around the central one and a finite resolution time of the detecting system, the formula is:

$$G_k(1) = \sum_N S_{kN} \cos N\,\omega t\, e^{-\delta\omega N t}\, e^{-1/2(\omega N\tau)^2}$$

δw = absolute frequency spread

τ = resolution time of system

The fitting is done to

$$a_k(t) = G_k(t)\, a_k(0) + c,$$

where c is a time-independent constant.

Procedure

The program is split up in three parts

(a) 'Data'. This part reads in the data from magnetic tape unit number 1 and calculates the a_k coefficients as a function of time. The input data consist of the time spectrum for the region of interest and the appropriate background spectrum, both should be in the same run on the tape. It is possible that there are two angles in one run. After reading in data for a least two angles, it orders the data into groups (maximum of 512) and fits each group to $W(\theta)=\Sigma_k a_k P_k(\cos\theta)$ for K=0,2,4.
If desired a list of calculated values and their errors is printed out (time runs backwards on this list).
The search for next runs is according to run number, i.e. a higher run number causes a search forward of the tape and a lower search backwards. By reading in a faked high or low run number with a blank card behind it, it is possible to direct the search freely without changing the data.

(b) 'Display' The central processing and fitting unit. This part asks for the other information necessary for fitting to the formula.

(1) The out put from 'Data', i.e. $a_k(0)$ and the error in $a_k(0)$. After calculation of $a_k(0)$ and χ^2 it can be directed to all parts of the program (see listing in Table I). The program types after each step the number of channels used for the fit, the $a_k(0)$ value, its the error in $a_k(0)$ and the χ^2.

(c) 'Sun' This part calculates the S_{kN} coefficients and the values of N for formula (1) as function of spin, n and k. It calculates the matrix and diagonalizes it with the method of Jacobi then it calculates S_{kN} for each N, making use of the fact that for each n only half of the magnetic substates contribute.

Table I List of options in 'Display' on question '0'

0. Types out all possibilities.
1. Goes to 'Data' and read in new set of data.
2. Goes to 'Sun' and asks for new values of k, spin and n and recalculates S_{kN} and N.
3. Print out all relevant parameters, e.g. S_{kN} coefficients, N-values, $a_k(0)$, error in $a_k(0)$, χ^2, spin, n, k first and last channel of the region of fitting, time-zero, frequency, spread in frequency and fudge.
4. Asks for new value of time-zero.
5. Asks for new region of fitting.
6. Asks for a new frequency, constant term and relative spread.
7. Goes to show-routine, which shows experimental data with upper and lower limit of the error bar, the calculated curve and the zero line

if the upper and lower limits (amax and amin) contain zero. To leave this routine set breakpoint 4.

8. Goes to the plotting routine, if and only if the program has displayed the data after the last calculation, otherwise it does the same as 7.

9. Goes to the plotting routine, taking old values for the plotting parameters except for YOFF, unless they are zero, in which case it goes to 7.

Input for Data

Card I: NGRP, NCPG, NLEG, IDIR, TITLE (FORMAT 414, 10A4).

NGRP number of groups less than 513.

NCPG number of channels per group NGRP * NCPG $\leq$ 1024.

NLEG number of Legendre polynomials (maximum 3).

IDIR direction first search (0 forward, 1 backward).

Title (less than 40 characters).

Card II: Date, Month, Year Run, Angle

Format 413, F6.0.

Year = 0 calculations follows.

Card III: IBASE, ZNORM

FORMAT 15, F7.3

IBASE: First Channel of spectrum to be read.

ZNORM: Normalization constant with which the data are multiplied before processing. ZNORM<0 Background

ZNORM>0 Real data

ZNORM = 0 go to next angle.

So proper order is:

I, II, III (background), III(real data), III(blank), II, III(background), III(real data),III(blank), II(blank)

Teletype input

PRINT YES(1) OR NO (0) (I1)

1: PRINTS out ALL a_k for each group normalized to a_o=1 and not normalized with group number, error in a_k and χ^2 of fit for each group.

0: Suppresses this output, and this information is lost, except for the nomalized values, which are used by 'DISPLAY' and may be plotted.

ENTER 1 TO RESTART, 0 TO EXIT (I1)

1: Begins again at the beginning of the program (reread all data)

0: Stops

Resolution Time (FWHM)

Floating point input of the resolution time of the electronics and detector expressed in number of groups.

FREQ IN RAD/GR, C, REL SPREAD

Format 3F10.0

Asks for the essential parameters in the formulae, the frequency being ω_q and relative spread being $\frac{\delta\omega}{\omega_q}$

TZ(F 10.0)

Input of time zero, as group number according to the output listing of 'Data'.

AMIN, AMAX

The lower and upper limit of the values for the show-routine and for the plot routine. Values outside this region are set to the upper or lower limit.

GROUPS/INCH, YSC, YOFF (Floating point)

GROUPS/INCH X-scale

YSC, number of inches over which the y-scale extends.

YOFF, vertical offset of AMIN in inches, zero being point of pen location.

EXP(1) CAL(2), AXIS(3), SLEW(4), DONE(5)

Format I1

1. Plots experimental error bars.
2. Plots the current theoretical curve.
3. Plots the x-and y-axis, from time-zero to the last channel to plot and the y-axis from amin to amax, and x-axis at a_k=0 and the y-axis on time =0.
4. Slews the paper up till the second integer inch after the plot and cannot be returned.
5. Returns to the rest of the program.

Plot same as above

Other questions are self-explanatory.

All input parameters are floating point unless otherwise indicated.

References

1. C.W. Luursema, Thesis University of Alberta (October 1975).

2. H. Frauenfelder and R. Steffen, In α, β and γ ray Spectroscopy. Ed. K. Siegbahn, North-holland Publishing Co. A'dam ('65).

3. H. Haas and D.A. Shirley, Journal of Chemical Physics 58, 3339 ('73).

4. E. Matthias, W. Schneider and R.M. Steffen, Physics Letters 4, 41 ('63).

5. E. Bodenstedt, In 'Angular Correlations in Nuclear Disintegration'. Rotterdam University Press, Groningen, Nederland, Ed. H. van Krugten and B. van Nooyen ('71).

LISTING OF THE PROGRAM

```
 1  C     LINK 1
 2  C      DATA
 3  C
 4  C     FITTING DATA TO ANGULAR DISTRIBUTIONS
 5  C      FIRST OF THRE PROGRAMS TO HANDLE DATA
 6  C      OF PERTURBED ANGULAR DISTRIBUTION DUE TO EFG
 7  C
 8           DIMENSION TITLE(10),WMAT(3,3,171),DVEC(4,512),KS(1024)
 9           DIMENSION INFO(26),X(3),WINV(3,3),A(3),ERR(3)
10           DIMENSION SUMSQ( 512)
11           DIMENSION DUM(1691),DSTO(4,171)
12           COMMON DUM,CRAP,AKP,NI,IT,TZ,SIP,ICL,ICU,W,FUD,SPR,NGRP,ETA
13           EQUIVALENCE (DUM(1),WMAT(1),DSTO(1))
14           EQUIVALENCE (VAR,TEMP)
15  C
16  C
17  1000   CONTINUE
18  5001   TYPE 6001
19  C
20  C      OUTPUT LIST
21  C
22  6001    FORMAT ($PRINT NO(0),YES(1)$)
23           ACCEPT 6002,IK
24  6002   FORMAT (I1)
25  C
26  C       READ MAIN PARAMETERS
27  C
28           READ 200,NGRP,NCPG,NLEG,IDIR,(TITLE(I),I=1,10)
29  200     FORMAT(4I4,10A4)
30           PRINT 220,NGRP,NCPG,NLEG,IDIR
31  220     FORMAT(1H1,I3,$ GROUPS $,I3,$ CH/GRP  $,I1,$ POLYS  $,I1,$ F/R$)
32           IF(NGRP)1,1,2002
33  1        STOP
34  C
35  C      CHECK SIZES OF THINGS
36  C
```

```
      2002  KSSIZE=NGRP*NCPG
            IF(NGRP-512)2003,2003,180
      2003  IF(KSSIZE-1024)2004,2004,181
      2004  IF(NLEG-3)2005,2005,182
      2005  IF(IDIR-1)2006,2006,183
      2006  IF (IDIR) 6010,6010,6011
      6010  IRUN=0
            GOTO 6012
      6011  IRUN=1000.
      6012  CONTINUE
      C
      C     INITIALIZE MATRICES
      C
            DO 61 J=1,512
            DVEC(4,J)=0.
      61    SUMSQ(J)=0.
            ZHOLD=0.
            DO 9 L=0,2
            CALL MEMSWT(L+5)
            DO 9 I=1,171
            IP=I+L*171
            DO 8 J=1,3
            DO 7 K=1,3
      7     WMAT(K,J,I)=0.
      8     DVEC(J,IP)=0.
      9     CONTINUE
      C
            CALL INITKS(1,KS,KSSIZE)
      C
      C     READ CARD FOR MIDDLE LOOP
      C
      10    READ 201,(INFO(J),J=3,6),THETA
            PRINT 221,(INFO(J),J=3,6),THETA
      201   FORMAT(4I3,F6.1)
      221   FORMAT(5X,$D,M,Y,RUN,ANGLE $,3I3,I5,2X,F6.1)
            IF(INFO(5)-1)30,30,2011
```

```
 2011   THETA=3.1416*THETA/180.
        YX=COS(THETA)
        YX=YX*YX
        X(1)=1.
        X(2)=1.5*YX-0.5
        X(3)=0.125*(35.*YX*YX - 30.*YX + 3.0)
 6003   IS=1
        IF (INFO(6)-IRUN)6004,6004,6005
 6004   IS=3
 6005   IRUN=INFO(6)
 C
 C      READ CARD FOR INNER LOOP
 C
 20     READ 202,IBASE,ZNORM
 202    FORMAT(I5,F7.3)
        PRINT 222,IBASE,ZNORM
 222    FORMAT(10X,I5,2X,F7.3)
        IF(ZNORM-0.)219,21,22
 21     GO TO 10
 219    ZHOLD=ZNORM
 22     CALL READKS(IS,IBASE,INFO,IERR)
        IF(IERR-2)23,184,184
 23     IS=3
 C
 C      DATA READ IS OK, NOW PROCESS IT
 C
        DO 29 L=0,2
        CALL MEMSWT(L+5)
        DO 29 IP=1,171
        I=IP+L*171
        IF (NGRP-I)20,2023,2023
 2023   IBEG=(I-1)*NCPG+1
        IEND=IBEG+NCPG-1
        SUM=0.
        DO 2024 J=IBEG,IEND
 2024   SUM=SUM+FLOAT(KS(J))
```

,

```
109          IF(ZN0RM)241,21,249
110   241    DVEC(4,I)=SUM
111          G0 T0 29
112   249    VAR=ZN0RM*ZN0RM*SUM+ZH0LD*ZH0LD*DVEC(4,I)
113          SUM=SUM*ZN0RM+DVEC(4,I)*ZH0LD
114          IF(VAR-10.)25,26,26
115   25     VAR=10.
116   26     D0 28 J=1,NLEG
117          DVEC(J,I)=DVEC(J,I)+SUM*X(J)/VAR
118          D02027 K=1,NLEG
119   2027   WMAT(K,J,IP)=WMAT(K,J,IP)+X(J)*X(K)/VAR
120   28     C0NTINUE
121          SUMSQ(I)=SUMSQ(I)+SUM*SUM/VAR
122          DVEC(4,I)=0.
123   29     C0NTINUE
124          G0 T0 20
125   C
126   C
127   C      INVERT MATRIX, CALC. C0EFFS AND ERR0RS
128   C
129    30    IF (IK)  4004,4004,4003
130   4003   PRINT 203,(TITLE(I),I=1,10)
131   203    F0RMAT(10A4,/,/,$ GR0UP  A0      ERR    A2      ERR    A4      ERR$)
132   4004   TYPE 4008,(TITLE(I),I=1,10)
133   4008   F0RMAT(10A4)
134          D0 50 L=0,2
135          CALL MEMSWT(L+5)
136          D0 50 K=1,171
137          KA=K+L*171
138          IF (NGRP-KA) 51,4002,4002
139   4002   G0 T0 (2031,  32,33),NLEG
140   2031   DET=WMAT(1,1,K)
141          IF(DET)311,485,311
142   485    PRINT 207,KA
143   207    F0RMAT(1X,I3,$  MATRIX SINGULAR$)
144          G0 T0 50
```

```
311     WINV(1,1)=1./DET
        GO TO 34
32      DET=WMAT(1,1,K)*WMAT(2,2,K)-WMAT(1,2,K)*WMAT(2,1,K)
        IF(DET) 321,485,321
321     WINV(1,1)=WMAT(2,2,K)/DET
        WINV(2,1)=-WMAT(1,2,K)/DET
        WINV(1,2)=WINV(2,1)
        WINV(2,2)=WMAT(1,1,K)/DET
        GO TO 34
33      COF11=WMAT(2,2,K)*WMAT(3,3,K)-WMAT(2,3,K)*WMAT(3,2,K)
        COF12=WMAT(2,3,K)*WMAT(3,1,K)-WMAT(2,1,K)*WMAT(3,3,K)
        COF13=WMAT(2,1,K)*WMAT(3,2,K)-WMAT(2,2,K)*WMAT(3,1,K)
        COF22=WMAT(1,1,K)*WMAT(3,3,K)-WMAT(1,3,K)*WMAT(3,1,K)
        COF23=WMAT(1,2,K)*WMAT(3,1,K)-WMAT(1,1,K)*WMAT(3,2,K)
        COF33=WMAT(1,1,K)*WMAT(2,2,K)-WMAT(1,2,K)*WMAT(2,1,K)
        DET=WMAT(1,1,K)*COF11 + WMAT(1,2,K)*COF12 + WMAT(1,3,K)*COF13
        IF(DET)331,485,331
331     WINV(1,1)=COF11/DET
        WINV(1,2)=COF12/DET
        WINV(2,1)=WINV(1,2)
        WINV(1,3)=COF13/DET
        WINV(3,1)=WINV(1,3)
        WINV(2,2)=COF22/DET
        WINV(2,3)=COF23/DET
        WINV(3,2)=WINV(2,3)
        WINV(3,3)=COF33/DET
C
34      DO 36 I=1,NLEG
        A(I)=0.
        DO 35 J=1,NLEG
35      A(I)=A(I)+WINV(I,J)*DVEC(J,KA)
36      ERR(I)=SQRT(WINV(I,I))
C
C       CALCULATE CHI**2
        CHISQ=0.
        DO 362 I=1,NLEG
```

```
      SUM=0.
      DO 361 J=1,NLEG
361   SUM=SUM+WMAT(I,J,K)*A(J)
362   CHISQ=CHISQ+SUM*A(I) - 2.*A(I)*DVEC(I,KA)
      CHISQ=CHISQ+SUMSQ(KA)
C
C     PRINT RESULTS
C
      IF (IK) 4006,4006,4005
4005  PRINT 204,KA,(A(I),ERR(I),I=1,NLEG),CHISQ
204   FORMAT(1X,I3,2X,4(F8.1,1X,F5.1,1X))
4006  IF(A(1)-0.)50,50,37
37    IF(NLEG-1)50,50,38
38    DO 41 J=2,NLEG
      TEMP=A(J)*A(J)*WINV(1,1)/A(1)**4 -2.0*A(J)*WINV(1,J)/A(1)**3
     1 +WINV(J,J)/A(1)**2
      IF(TEMP)39,39,40
39    TEMP=9801.
40    ERR(J)=SQRT(TEMP)
41    A(J)=A(J)/A(1)
      DVEC(3,KA)=A(3)
      DVEC(1,KA)=A(2)
      DVEC(2,KA)=ERR(2)
      DVEC(4,KA)=ERR(3)
      IF (IK) 50,50,4007
4007  PRINT 205,(A(J),ERR(J),J=2,NLEG)
205   FORMAT( 9X,$1.0$,8X,2(F8.3,1X,F5.3,1X))
50    CONTINUE
C
C      STORE RESULTS FOR NEXT PARTS
C
51    CALL MEMSWT(4)
      DO 400 K=1,NGRP
      DO 401 I=1,4
401   DST0(I,K)=DVEC(I,K)
400   CONTINUE
```

```
217          CALL MEMSWT(3)
218          IF (IT)500,500,501
219   501    CALL LINK(2)
220   500    CALL LINK(3)
221   C
222   C      SUNDRY ERR0R MESSAGFES
223   C
224   180    TYPE 230
225   1801   TYPE 231
226           ACCEPT 6002,IN
227          IF(IN-1) 1,1000,1
228   231     F0RMAT($ ENTER 1 T0 RESTART, 0 T0 EXIT (I1)$)
229   230    F0RMAT($ 512 GR0UPS MAX $)
230   C
231   181    TYPE 232
232   232    F0RMAT($ 1024 MAX T0TAL CHANNELS$)
233          G0 T0 1801
234   182    TYPE 233
235   233    F0RMAT($ 3 LEGENDRE P0LYS. MAX $)
236          G0 T0 1801
237   183    TYPE 234
238   234    F0RMAT($ DIRECTI0N C0NTR0L MUST BE 0 0R 1 $)
239          G0 T0 1801
240   184    TYPE 235,IERR
241   235    F0RMAT($ TAPE READ ERR0R $,I2)
242          G0 T0 1801
243          END
```

```
C       LINK 2
C      DISPLAY
C
C      FIT TO FORMALA FOR QUADRUPOLE INTERACTION PERTUBATION
C       AND OUTPUT ROUTINES
C
       DIMENSION KC(512),IR(6),KSADR(4),LIST(5),IREP(4),IORG(4),IFRO(4)
       DIMENSION IOAC(4)
        DIMENSION DVEC(4,171),SKN(106),XN(106)
       DIMENSION KB(512),KL(512),KU(512)
       DIMENSION SUN(106),XUN(106)
       DIMENSION DUM(1691)
       COMMON DUM,CRAP,AK ,NN,IT,TZ,SI ,ICL,ICU,W,FUD,SPR,NGRP,ET
       EQUIVALENCE(DUM(1),DVEC(1),SUN(1))
       EQUIVALENCE(DUM(107),XUN(1))
       EQUIVALENCE (DUM(358),TR)
C
C      2ND OF 3 PROGRAMS TO HANDLE DATA OF TDPAD
C
       TYPE 108
108    FORMAT ($RESOLUTION TIME (FWHM)$)
       ACCEPT 102,TR
       TR=TR/2.3548
       IF (IT) 5006,5006,4999
C
5006   TYPE 103
       CALL MEMSWT(3)
       ACCEPT 102,W,FUD,SPR
103    FORMAT($FREQ IN RAD/GROUP, CONST, REL SPREAD $)
C
4999   DO1 I=1,NN
       SKN(I)=SUN(I)*EXP(-.5*(W*XUN(I)*TR)**2)
1      XN(I)=XUN(I)
       CALL MEMSWT(4)
       IF (IT) 5004,5004,5000
C
```

```
C      GOTO PROGR 1 DATA INPUT AND A2/A4 CALCULATION
C
5001   CALL MEMSWT(3)
       CALL LINK(1)
C
C      GOTO PROGR 3 CALCULATION OF SKN COEFF.
C
5002   CALL MEMSWT(3)
       CALL LINK(3)
102    FORMAT(10F10.5)
101    FORMAT( I3,F10.0)
C
C     PRINT OUT RELEVANT PARAMETERS
C
5003   PRINT 155,SI,ET,AK
155    FORMAT(/,6H SPIN= , F4.1,6H  ETA= ,F6.3,6H     K=,I1)
       PRINT 151,NN
151    FORMAT($ NUM FREQ=$ ,I3)
       PRINT 201
201    FORMAT(/,$XN(I)$)
       PRINT 102,(XN(I),I=1,NN)
       PRINT 202
202    FORMAT(/,$SKN(I)$)
       PRINT 102,(SKN(L),L=1,NN)
       PRINT 156,TZ,ICL,ICU,W,SPR,FUD
156    FORMAT(5H  TZ=,F5.1,6H  ICL=,I3,6H  ICU=,I3,4H  W=,F7.3,6H  SPR=,
      1 F4.3,6H  FUD=,F4.3)
       PRINT 104,AZ,DAZ,CHI
       GOTO 5013
C
C       INPUT TIMEZERO, ACCORDING TO  OUTPUT LIST OF A2/A4
C
5004   TYPE 5100
5100   FORMAT ($TZ (F10.0)$)
       ACCEPT 5110,TZ
5110   FORMAT (F10.0)
```

```
      TZ =NGRP-TZ
      IF (IT) 5005,5005,5000
C
5005  TYPE 4001
4001  FORMAT($ LOWER, UPPER GROUP   FOR FITTING$)
      ACCEPT 4002, ICL,ICU
4002   FORMAT(2F5.0)
C
C    FITTING CALCULATION
5000  SQ=0.
      AB=0.
      DVEB=0.
      P=IFIX(AK+.1)
      WMAB=0.
      NF=ICU-ICL+1
      DO 4 J=NGRP-ICU+1,NGRP-ICL+1
      WT=(FLOAT(J-1)-TZ)*W
      CAL=0.
      I=NGRP-J+1
C
C       CAST OUT ZERO ERRORS
C
      IF (DVEC(P,I))2,6,2
2     DO 3 N=1,NN
3     CAL=CAL+SKN(N)*COS(XN(N)*WT)*EXP(-XN(N)*SPR*WT)
      SQ=SQ+((DVEC(P-1,I)-FUD)/DVEC(P,I))**2
      DVEB=DVEB+(DVEC(P-1,I)-FUD)*CAL/DVEC(P,I)**2
      WMAB=WMAB+(CAL/DVEC(P,I))**2
      GOTO 4
6     NF=NF-1
4     CONTINUE
      AZ=DVEB/WMAB
      DAZ=SQRT(1./WMAB)
      CHI=SQ+AZ*AZ*WMAB-2.*DVEB*AZ
      TYPE 107,NF
107   FORMAT(6H   NF=,I3)
```

```
109           TYPE 104,AZ,DAZ,CHI
110   104     FORMAT($ T=0 COEFF,ERROR $,2F7.3,$  CHI**2=$,F7.1)
111   C
112   C       WHAT TO DO NEXT
113   C
114           IT=1
115   5013    TYPE 105
116   105     FORMAT  ($0$)
117   5012    ACCEPT 106,IJ
118   106     FORMAT(I1)
119           IJ=IJ+1
120           GOTO(5010,5001,5002,5003,5004,5005,5006,5007,5008,5009),IJ
121   5010    TYPE 5011
122   5011    FORMAT($DATA(1),S(K,N) (2),PRINT (3),TZ (4),FIT REGION (5),FREQ.
123          1 (6),SHOW (7),PLOT (8),PLOT (9),(I1)$)
124           GOTO 5012
125   C
126   C       DISPLAY DATA AND FITTED VALUES
127   C
128   5007    TYPE 110
129   110     FORMAT($ AMIN,AMAX $)
130           ACCEPT 102, AMIN,AMAX
131   11      IF(AMIN*AMAX)12,12,14
132   12      DO 13 J=1,NGRP
133   13      KB(J)=IFIX(-1000.*AMIN/(AMAX-AMIN))
134   14      DO2023J=1,NGRP
135           I=NGRP-J+1
136           XX=DVEC(P-1,I)+DVEC(P,I)
137           IF (XX-AMIN) 6015,6016,6016
138   6015    XX=AMIN
139   6016    IF (AMAX-XX) 15,16,16
140   15      XX=AMAX
141   16      KU(J)=IFIX(1000.*(XX-AMIN)/(AMAX-AMIN))
142           XX=DVEC(P-1,I)-DVEC(P,I)
143           IF (AMAX-XX) 6017,6018,6018
144   6017    XX=AMAX
```

```
      6018  IF (XX-AMIN) 17,18,18
      17    XX=AMIN
      18    KL(J)=IFIX(1000.*(XX-AMIN)/(AMAX-AMIN))
            WT=(FLOAT(J-1)-TZ)*W
            XX=0.
            DO 19 N=1,NN
      19    XX=XX+AZ*SKN(N) *COS(XN(N)*WT)*EXP(-XN(N)*SPR*WT)
            XX=XX+FUD
            IF(XX-AMIN)2020,2021,2021
      2020  XX=AMIN
      2021  IF(AMAX-XX)2022,2023,2023
      2022  XX=AMAX
      2023  KC(J)=IFIX(1000.*(XX-AMIN)/(AMAX-AMIN))
            KSADR(1)=LOCF(KC(1))
            KSADR(2)=LOCF(KU(1))
            KSADR(3)=LOCF(KL(1))
            KSADR(4)=LOCF(KB(1))
            DO 24 J=1,4
            IREP(J)=1
            IORG(J)=0
            IFRO(J)=0
            IBAC(J)=NGRP
      24    LIST(J)=J
            LIST(5)=0
            IF(AMIN*AMAX)2026,2026,2025
      2025  LIST(4)=0
      2026  IREP(1)=2
            CALL SHOSET(IREP,IORG,KSADR,IFRO,IBAC)
      27    CALL SHOW(0,LIST,IR)
            IF(IR(2))5,2028,2028
      2028  LIST(4)=0
            IF(IR(1))2029,2029,2026
      2029  LIST(4)=4
            GO TO 27
      5     IT=2
            GOTO 5013
```

```
C
C     PLOT ROUTINE
C
5008  IF (IT-1) 5000,5007,129
129   TYPE 131
131   FORMAT($ GROUPS/INCH, YSC,YOFF $)
      ACCEPT 102,GPI,YSC,YOFF
      TYPE 4101
4101  FORMAT($FIRST AND LAST GROUP   TO PLOT$)
      ACCEPT 4102, ICK,ICV
4102  FORMAT (2F5.0)
5700  TYPE 130
130   FORMAT($ EXPT(1) OR CAL(2), AXIS(3), SLEW (4), DONE(5)$)
      GOTO 5720
31    TYPE 5710
5710  FORMAT ($PLOT$)
5720  ACCEPT 106,IJ
      IF(IJ*(6-IJ))5700,5700,2032
2032  GOTO (2033,2050,5500,5600,5013),IJ
C
C     PLOT EXPERIMENTAL VALUES
C
2033  DO 2034 J=NGRP-ICV+1,NGRP-ICK+1
      XX=(-TZ+FLOAT(J-1))/GPI
      IX=IFIX(200.*XX)
      XX=YOFF+(FLOAT(KL(J))/1000.)*YSC
      IY=IFIX(200.*XX)
      IFC=0
      CALL DRAW(IFC,IX,IY,M)
      IF (M*(3-M)) 2331,2331,65
2331  IFC=1
      XX=YOFF+(FLOAT(KU(J))/1000.)*YSC
      IY=IFIX(200.*XX)
      CALL DRAW(IFC,IX,IY,M)
      IF(M*(3-M))2034,2034,65
2034  CONTINUE
```

```
      GO TO 65
C
C     PLOT CALCULATED VALUES
C
2050  TYPE 150
150   FORMAT($ POINTS/GROUP $)
      ACCEPT 102,PPG
      WTP=W/PPG
      NTOT=IFIX((FLOAT(NGRP-ICK)-TZ)*PPG)
      IFC=0
      DO 56 J=1,NTOT
      XT=FLOAT(J-1)*WTP
      XX=0.
      DO 51 N=1,NN
51    XX=XX+AZ*SKN(N) *COS(XN(N)*XT)*EXP(-XN(N)*SPR*XT)
      XX=XX+FUD
      IF(XX-AMIN)52,52,53
52    XX=AMIN
53    IF(AMAX-XX)54,55,55
54    XX=AMAX
55    XX=YOFF+(XX-AMIN)*YSC/(AMAX-AMIN)
      IY=IFIX(200.*XX)
      IX=IFIX(200.*FLOAT(J-1)/(PPG*GPI))
      CALL DRAW(IFC,IX,IY,M)
      IFC=1
      IF(M*(3-M))56,56,65
56    CONTINUE
      GOTO 65
C
C     PLOT AXIS
C
5500  XX=YOFF
      IY=IFIX(200.*XX)
      IX=0
      IFC=0
      CALL DRAW(IFC,IX,IY,M)
```

```
      IF (M*(3-M)) 5510,5510,65
5510  XX=Y0FF+YSC
      IY=IFIX(200.*XX)
      IFC=1
      CALL DRAW(IFC,IX,IY,M)
      IF (M*(3-M)) 5520,5520,65
5520  XX=Y0FF-AMIN*YSC/(AMAX-AMIN)
      IY=IFIX(200.*XX)
      IFC=0
      CALL DRAW(IFC,IX,IY;M)
      IF (M*(3-M))5530,5530,65
5530  XX=(NGRP-TZ-ICK)/GPI
      IX=IFIX(200.*XX)
      IFC=1
      CALL DRAW(IFC,IX,IY,M)
C
C
65    IFC=0
      IX=0
      IY=0
      CALL DRAW(IFC,IX,IY,M)
      GOTO 31
C
C     SLEW PAPER
C
5600  XX=(NGRP-TZ-ICK)/GPI
      IX=IFIX(XX+3)
      IX=200*IX
      IY=0
      IFC=2
      CALL DRAW(IFC,IX,IY,M)
      IF (M*(3-M)) 31,31,65
C
C     PLOT WITHOUT CHANGING GPI,YSC AND CHANNELS
C
5009  IF (GPI) 5007,5008,5900
```

```
289   5900   TYPE 5901
290   5901   FORMAT($YOFF$)
291          ACCEPT 102,YOFF
292          GOTO 31
293          END
```

```
C       LINK  3
C     SUN
C
C  CALCULATION OF SKN COEFFICIENTS AS FUNCTION OF SPIN AND ETA
C     FOR NON-AXIAL SYMMETRIC EFG
C     THIRD PROGRAM OF THREE TO HANDLE DATA
C
      DIMENSION CL(15,9)
      DIMENSION H(15,15),U(15,15),VALU(15)
      DIMENSION XV(106),SKN(106)
      DIMENSION DUM(1691)
      COMMON DUM,CRAP,AKP,NI,IT,TZ,SIP,ICL,ICU,W,FUD,SPR,NGRP,ET
       EQUIVALENCE (DUM(1),SKN(1))
       EQUIVALENCE(DUM(107),XV(1))
       EQUIVALENCE(DUM(215),CL(1))
C
C     PARAMETERS MATCHED WITH OTHER PARTS
C
5002  TYPE  3003
3003  FORMAT($A2 (2) OR A4 (4) (I1)$)
      ACCEPT 3001,(AK)
3001  FORMAT (I1)
C
100   TYPE 101
101   FORMAT($SPIN,ETA$)
      ACCEPT 102,SI,ET
102   FORMAT(2F10.0)
      N=2*SI+1.1
C
C   CALCULATE HAMILTONIAN
C
      DO 1600 I=1,15
      DO 1600 J=1,15
1600   H(I,J)=0
      DO 1650 I=1,(2*SI+1)
1650  H(I,I)=3*(I-SI-1)**2.-SI*(SI+1)
```

```
      DO 1680  I=1,(2*SI-1)
       H(I,I+2)=.5*SQRT((I+1)*(I)*(2*SI-I+1)*(2*SI-I)) *ET
1680   H(I+2,I)=H(I,I+2)
C
C  DIAGONALIZATION OF HAMILTONIAN
C     GIVES EIGENVALUES AS ROWA
C
      DO 20 I=1,N
      DO 20 J=1,N
20    U(I,J)=0
      DO 30 I=1,N
30    U(I,I)=1.
89    ITALY=0
      NMIN1=N-1
      DO 220 L=1,NMIN1
      LPLUS1=L+1
      DO 220 M=LPLUS1,N
      OFF=H(L,M)
      SPLIT=H(L,L)-H(M,M)
       Q=ABS(OFF)
      R=ABS(SPLIT)
      IF(10**6*Q-R-1.0E-24) 220,110,110
110   IF (SPLIT) 112,111,112
 111  S=SIGN(0.5,OFF)
      GOTO 130
112   IF (2.*Q-R) 116,113,113
113   S=SIGN(0.5,OFF*SPLIT)
      GOTO 130
116   S=OFF/SPLIT
130   C=SQRT(1.0-S*S)
C
C   LEFT MATRIX MULTIPLICATION
C
      DO 173 J=1,N
      X=C*H(L,J)+S*H(M,J)
      H(M,J)=C*H(M,J)-S*H(L,J)
```

```
 173   H(L,J)=X
C
C  RIGHT MATRIX MULIPLICATI0N
C
       D0 210 I=1,N
       X=C*H(I,L)+S*H(I,M)
       H(I,M)=C*H(I,M)-S*H(I,L)
       H(I,L)=X
       X=C*U(I,L)+S*U(I,M)
       U(I,M)=C*U(I,M)-S*U(I,L)
 210   U(I,L)=X
       ITALY=ITALY+1
 220   C0NTINUE
       IF (ITALY) 250,250,89
 250    D0 260  I=1,N
 260   VALU(I)=H(I,I)
C
C
C       GLEBSCH-G0RD0N CALCULATI0N(SI M1,SI M2/K M3)
C
       SKN(1)=0.
       XV(1)=0.
       NI=1
       IF(AK-2.*SI-0.1)300,1400,1400
 300   C0NTINUE
C
C     SAME K AND SPIN D0N,T CALCULATE CLEBSCH-G0RD0N'S
C
       IF (ABS(AK-AKP)+ABS(SI-SIP)) 450,550,450
 450   AKP=AK
       SIP=SI
       D0 500  AM1=-SI,SI
       D0 500 AM3=-AK,AK
 500   CL(IFIX(SI+AM1+1.1),IFIX(AK+AM3+1.1))=
      1     CG(SI,AM1,SI,AM3-AM1,AK,AM3)
C
```

```
109   C     CALCULATE FREQUENCIES
110   C
111   550    I=1
112          DO 800 NN=1,N
113          DO 780 NP=1,NN
114          I=I+1
115          XV(I)=ABS(VALU(NN)-VALU(NP))
116          P=0.
117          DO 730 AM3=-AK,AK
118          JKM3=IFIX(AK+AM3+1.1)
119          DO 710 AM1=-SI,SI
120          JIM1=IFIX(SI+AM1+1.1)
121          IF(MOD(JIM1+NP,2))710,670,710
122   670    JIM2=IFIX(SI+AM1-AM3+1.1)
123          IF (MOD(JIM2+NN,2))710,675,710
124   675    T1=CL(JIM1,JKM3)*(-1.)**IFIX(SI+AM3-AM1+0.1)
125          T5=U(JIM2,NN)
126          T3=U(JIM1,NP)
127          DO 690 AM4=-SI,SI
128          JIM4=IFIX(SI+AM4+1.1)
129          IF (MOD(JIM4+NP,2)) 690,680,690
130   680    JIM5=IFIX(SI+AM4-AM3+1.1)
131          IF (MOD(JIM5+NN,2))690,685,690
132   685    T2=CL(JIM4,JKM3)*(-1.)**IFIX(SI+AM3-AM4+0.1)
133          T4=U(JIM4,NP)
134          T6=U(JIM5,NN)
135          P=P+T1*T2*T3*T4*T5*T6
136   690    CONTINUE
137   710    CONTINUE
138   730    CONTINUE
139   C
140   C      PUT THEM ON THE RIGHT SPOT
141   C
142          IF(NP-NN)732,735,732
143   732    P=2.*P
144   735    IF (XV(I)) 760,740,760
```

```
145   740    SKN(1)=SKN(1)+P
146          I=I-1
147          GOTO 780
148   760    SKN(I)=P
149   780    CONTINUE
150   800    CONTINUE
151          LIMIT=I
152   C
153   C      TAKING SAME ENERGIEDIFF. TOGETHER
154   C
155          DO 1100 I=2,LIMIT-1
156          IF(XV(I)+5.)1100,1010,1010
157   1010   DO 1050 J=I+1,LIMIT
158          IF (ABS(XV(I)-XV(J))-1.0E-4) 1020,1050,1050
159   1020   SKN(I)=SKN(I)+SKN(J)
160          SKN(J)=0.
161          XV(J)=-10.
162   1050   CONTINUE
163   1100   CONTINUE
164   C
165   C      CAST OUT ZERO AMPLITUDES
166   C
167          DO 1200 I=2,LIMIT
168          IF(ABS(SKN(I))-0.0001) 1200,1150,1150
169   1150   NI=NI+1
170          SKN(NI)=SKN(I)
171          XV(NI)=XV(I)
172   1200   CONTINUE
173   C
174   C      MAKE THEM PROPRE
175   CC
176   1300   CONTINUE
177   1320   DO 1330 L=1,NI
178          XV(L)=XV(L)/(4.*SI*(2.*SI-1.))
179   1330   SKN(L)=SKN(L)/(2.*AK+1.)
180   1400   CONTINUE
```

```
      C
      C     GOTO DISPLAY PART
      C
            RETURN
            END
```

```
 1          FUNCTION CG(A,C,B,D,E,F)
 2          DIMENSION FACT(26)
 3    C     COMPUTES CLEBSCH-GORDAN COEFFS (J',M',J'',M''/J,M)
 4    C     DEFINITION IS THAT OF M.E.ROSE
 5          IF(ABS(FACT(3)-0.693)-0.002) 2,1,1
 6    1     CALL FACTOR(FACT)
 7    2     CG=0.0
 8          IF(B-ABS(D)+0.1)99,99,32
 9    32    IF(A-ABS(C)+0.1)99,99,34
10    34    IF(E-ABS(F)+0.1)99,99,44
11    44    IF(ITRI(A,B,E))3,99,3
12    3     IF(ABS(C+D-F)-0.1)4,99,99
13    4     I1=A+C+0.1
14          I2=A-C+0.1
15          I3=B+D+0.1
16          I4=A+B-E+0.1
17          I5=B-E-C+0.1
18          I6=A+D-E+0.1
19    C     CALCULATE LIMITS OF THE SUM
20          ISTART=MAX(0,I5,I6)
21          IEND=MIN(I2,I3,I4)
22          IF(IEND-ISTART)99,5,5
23    5     I4=B-D+0.1
24          I5=E-F+0.1
25          I6=E+F+0.1
26          S=0.0
27    C     NOW DO THE SUM
28          DO 10 I=ISTART,IEND
29          RI=FLOAT(I)
30          J1=E+RI+C-B+0.1
31          J2=E+RI-A-D+0.1
32          J3=A+B-E-RI+0.1
33          J4=A-RI-C+0.1
34          J5=B+D-RI+0.1
35          T1=FACT(I+1)+FACT(J1+1) + FACT(J2+1)+FACT(J3+1) + FACT(J4+1)
36          T1=T1+FACT(J5+1)
```

```
37          RI=(-1)**I
38          S=S+RI*EXP(-T1)
39    10    CONTINUE
40          T1=FACT(I1+1)+FACT(I2+1)+FACT(I3+1)+FACT(I4+1)
41          T1=T1+FACT(I5+1)+FACT(I6+1)
42          CG=SQRT(DELTA(A,B,E,FACT)*EXP(T1))*SQRT(2.0*E+1.0)*S
43    99    RETURN
44          END
```

```
      FUNCTION DELTA(A,B,C,FACT)
      DIMENSION FACT(26)
      I1=A+B-C+0.1
      I2=B+C-A+0.1
      I3=A+C-B+0.1
      I4=A+C+B+1.1
      DELTA=FACT(I1+1)+FACT(I2+1)+FACT(I3+1)-FACT(I4+1)
      DELTA=EXP(DELTA)
      RETURN
      END
```

```
 1          FUNCTION ITRI(A,B,C)
 2  C       TESTS TRIANGLE INEQUALITY OF 3 ANGULAR MOMENTA
 3  C       ALSO REWUIRES INTEGER SUM TO GIVE VALID RETURN OF VALUE 1
 4  C
 5          ITRI=0
 6          IF(A+B+0.1-C) 99,2,2
 7  2       IF(ABS(A-B)-0.1-C)3,99,99
 8  3       S=A+B+C
 9          S1=FLOAT(INT(S+0.1))
10          IF(S-S1-0.1) 4,4,99
11  4       ITRI=1
12  99      RETURN
13          END
```

```
      SUBROUTINE FACTOR(FACT)
C
C     CALCULATE AND STORE FACTORIALS FOR C-G ROUTINES
C     ACTUALLY STORES LOG FACTORIALS
      DIMENSION FACT(26)
      FACT(1)=0.
      FACT(2)=0.
      DO 1 I=3,26
      RI=FLOAT(I-1)
1     FACT(I)=FACT(I-1) + ALOG(RI)
      CALL LINK(2)
      END
```